

Index

A

- Adhesive bonded joints, 527
- Aircraft wing load history, 265
- Almen strip, 94
- Arall (*see* Glare and Arall)

B

- Basquin relation, 144, 145, 204, CD-100
- Biaxial loading, 77–79, 118
- Block-program fatigue test, 308, 309
- Bolts loaded in tension, 511
 - modified bolt heads, 513
 - pre-tension of bolts, 514
 - screw thread, rolled, 512
- Bridge, 263, 579

C

- Case histories, failures in service:
 - blade spring failures, CD-77
 - compressor blade failure, 52, 53
 - driving shaft of a scooter, 48
 - driving shaft of rolling machine, 236
 - expansion coupling failure, CD-83
 - flap beam failure, 50
 - fuselage failure, 117, CD-87
 - helicopter blade failure, 52, CD-81
 - hole reinforcement, 576
 - lamp-post, 263, CD-85
 - landing gear case, CD-79
 - lug connection, CD-90
 - motor car axle failure, 33
 - motorcycle front wheel failure, 2, CD-74
 - pressure bulkhead failure, 475
 - reinforced hole problem, 576
 - repaired wing structure failure, 579
 - sharp corner in bracket, 81
 - single spar failure, 391
 - tiller of sailing boat, 34

- Tsing Ma bridge, 579
- turbine blade failures, 483
- Clipping of high-amplitude cycles (*see* Truncation of load spectrum)
- Coffin–Manson relation, 164, 316
- Combined loading:
 - cyclic tension and shear, 159
 - notch effect, 190
 - out-of-phase loading, 161
- Comparative fatigue tests:
 - comparative CA tests, 156
 - comparative service-simulation fatigue tests, 405
 - comparative tests on bolts, 380
- Composite materials, 591
- Constant ΔK -tests, 216
- Corrosion fatigue, 457–479
 - case history, 475
 - corrosion effect on:
 - crack growth, 462
 - crack initiation, 464
 - fatigue limit, 460
 - fracture surface appearance, 470–472
 - S-N curve, 461, 465
 - effect of:
 - corrosion pits 44
 - cycle wave shape, 46, 467
 - frequency, 45
 - holding at S_{\max} , 468, 469
 - water vapor, 462
 - fatigue in salt water, 45, 554
 - gaseous environments, 459, 462
 - liquid environments, 460, 464
 - practical aspects, 483
 - shift of knee of S-N curve, 44
- Crack closure, 225
 - crack closure equations, 229
 - crack closure measurement, 227, 413

- crack opening stress level, 227
 - crack tip shielding mechanisms, 233
 - effect on crack front shape, 231
 - effective ΔK (ΔK_{eff}), 228
 - effective ΔS (ΔS_{eff}), 228
 - Elber mechanism, 226
 - more crack closure near surface layer, 341
 - plane strain/plane stress, 230
 - plasticity induced crack closure, 225
 - Crack driving force, 240
 - Crack front:
 - crack front continuity, 19
 - curved crack front, 124
 - growth of oblique crack front, 250, 251
 - incompatible crack front orientation, 342
 - shape affected by crack closure, 231
 - Crack growth phenomenon (*see also* Striations):
 - crack front continuity, 19
 - crack growth mechanism, 39
 - structure-sensitive crack growth, 239
 - Crack growth period, 15, 36, 37
 - Crack growth prediction models VA loading, 351
 - Corpus, 356
 - crack closure models, 355
 - interaction models, 353
 - modified Corpus, 358
 - non-interaction model, 352
 - Onera, 358
 - primary/secondary plasticity, 364
 - Preffas, 358
 - strip yield models 359
 - verification criteria for prediction models, 361
 - Wheeler, 354
 - Willenborg, 354
 - yield zone models, 354
 - Crack growth resistance, 21, 234, 240
 - different heat treatments, 235, 237, 238
 - different materials, 234–239
 - Crack growth under VA loading (*see also* Crack growth prediction models):
 - crack growth retardation, 332–335, 339
 - delayed retardation, 339
 - incompatible crack front orientation, 342
 - initial fast crack growth, 348
 - load spectrum truncation effect, 349
 - non-interaction behaviour, 331
 - overload (OL) cycles, 332–335
 - sequence effect, 344–347
 - thickness effect, 335, 347
 - yield stress effect, 337
 - Crack initiation, 15–18
 - cyclic slip 16–18
 - extrusion, 16
 - free surface, 19–21
 - grain boundaries, 20
 - inclusions (*see* Inclusion)
 - intrusion, 16
 - micro-structural crack growth barriers, 29
 - reversed slip, 17
 - scatter, 35
 - Crack initiation period, 15–18, 21, 36, 37, 143, 202
 - Crack nucleation (*see* Crack initiation)
 - Crack opening displacement (COD), 226, 414
 - Crack tip:
 - crack tip opening, 414
 - crack tip plastic zone, 130
 - displacements under plane strain and plane stress, 128, 129
 - K -dominated zone, 131
 - Crystallographic aspects, 23
 - Cyclic creep, 166
- D**
- Design problems, 559–586
 - design against fatigue, 562–565, CD-93
 - case histories, 574–583
 - FE calculations, boundary conditions, CD-97
 - safety margins, 566
 - fatigue limit and safety factors, 567
 - finite fatigue life, CA-case, 569
 - finite fatigue life, VA-case, 570
 - safe crack growth by periodic inspection, 571
 - safety in a corrosive environment, 573
 - uncertainties, 566
 - survey of design issues, 560–562
- E**
- Edge notch, 70
 - Effective ΔK (ΔK_{eff}), 228
 - Elastic anisotropy, 24, 32
 - Elliptical hole, 34, 35

Environmental effects (*see* Corrosion fatigue)

F

Fatigue crack growth, 209

- crack growth arrest, 220–222
- small crack phenomenon, 220–222
- crack growth equations, 215, 223
- crack growth under combined tension and bending, 251
- description of test results, 211
- effect of:
 - different batches, 236
 - different material producers, 236
 - material thickness effect, 232
 - material yield stress, 235
 - stress ratio, 213
- regions I, II, III, 217
- semi-circular fatigue cracks, 237
- similarity concept, 211, 212
- structure-sensitive crack growth, 239
- threshold region, 218

Fatigue damage accumulation, 304

Fatigue diagram:

- lug, 503
- notched specimens, 182
- unnotched specimens, 147

Fatigue failures in service (*see also* Case histories):

- symptomatic or incidental failure, 390

Fatigue fracture surface (*see also* Striations):

- characteristic features, 48
 - microscopic features, 49
 - macroscopic features 51
- factory roof fracture 158
- growth bands, 52
- no macro plastic deformation, 51
- number of crack nuclei, 32, 35
- perpendicular to main principle stress, 53
- radial steps, 55
- shear lips, 54, 342, 471

Fatigue limit (S_f):

- notched specimens ($S_m = 0$), 173
- notched specimens ($S_m > 0$), 182
- predictions, 173, 195
- relation between S_f and S_U , 149, 150
- safety factor, 385
- threshold character, 143, 144

Fatigue notch factor (K_f), 174

Fatigue of joints (*see* adhesive bonded joints, lugs, riveted and bolted joints, tension bolt,

welded joints), 499

Fatigue tests, 395–418

- crack closure measurements, 413
- crack growth measurements, 408
 - potential drop technique, 410
 - marker loads, 412
- evaluation of test results, 406
- fractographic analysis, 406, 412
- full-scale fatigue tests, 400, CD-104
- purpose of fatigue tests, 396
- service-simulation fatigue tests, 287, 404
- specimens, 397, 402
- specimen clamping, 403
- step test for fatigue limit, 399
- why and how, CD-101

Fiber-metal laminates, 589

- crack bridging, 596
 - crack growth results, 602–606
 - fiber-metal laminate concept, 595
 - growth of small cracks, 600
- Fillet, 77

Final crack length, 243, 546, 570–572

Flight-simulation fatigue test, 289, 404

Frequency effects:

- corrosion fatigue 45, 463
- high temperature crack growth, 488

Fretting (corrosion), 437

- alleviation of fretting damage, 452
- avoiding fretting, 449
- effect on fatigue limit, 449
- fretting damage mechanism, 438
- fretting in lug, 447–449, 453
- mean stress effect, 446
- variables affecting fretting corrosion, 440

G

Gerber parabola, 152

Glare and Arall (*see also* Fiber-metal laminates), 589

- crack growth in Glare fuselage, 605
- cross ply Glare, 598
- fatigue of a Glare lug, 603
- fatigue of Glare riveted lap joints, 604
- residual strength, 605
- resistance against corrosion, fire and

impact, 607

Goodman relation, 152

H

Heywood approximation for K_t of central hole, 70

High-cycle fatigue, 145

High temperature fatigue, 481

– effect on:

– fatigue crack growth, 488

– fatigue limit, 486

– supersonic aircraft, 485

– thermal stress cycles, 483, 486

– turbine blades, 483

Hole reinforcement, 79, 576

Hysteresis loop, 146

Hysteresis loops and rainflow counts, 275

I

Inclusion:

– crack growth around inclusions, 32

– crack initiation at inclusion, 26

– influence on fatigue limit, 27

– non-metallic slag inclusions, 28

Initial crack length, 241, 546, 571

Interaction effects, 303

J

Joints (*see* adhesive bonded joints, lugs, riveted and bolted joints, tension bolt, welded joints)

K

K -dominated zone, 131

L

Laminated sheet material, 591

– crack growth in lugs, 592, 593

– crack growth in wing structure, 594, 595

– fatigue crack growth, 591–593

– slow growth of part through cracks, 593, 594

Lamp post, 263, CD-85

Leak before break, 249, 552, 553

Load cycle counting methods:

– level crossing method, 267

– rainflow count method, 273

– range count method, 271

– two-dimensional load range counting, 272

Load sequence effect:

– LoHi compared to HiLo, 300, 301, 306–310

– notch root plasticity effect, 301

– random and block-program sequence, 345, 346

– sequence effect in block-program tests, 309, 310

– sequence in overload cycles, 308

Load spectra (*see also* Random load), 259, 293

– determination of load spectrum, 280

– design life time, 281

– mission analysis, 285

– strain gage measurements, 286, 579, 582, 583

– deterministic loads, 266

– irregularity factor, 270

– loads in service 261

– (non-)stationary load histories, 266

– (non-)symmetric load histories, 268, 269

– shape of load spectrum

– flat load spectrum, 271

– steep load spectrum, 271

– stochastic loads, 266

– truncation (*see* Truncation of load spectrum)

Low cycle fatigue, 146, 147, 161

– Coffin–Manson relation, 165

– cyclic strain hardening, 162, 163

– cyclic strain softening, 162, 163

Low temperature fatigue, 490–492

– effect on the fatigue strength, 491

– effect on fatigue crack growth, 491

– transition from ductile failure to brittle failure, 493

Lug, 74, 501

– crack growth in a lug, 244

– fatigue diagram, 503

– fatigue strength calculation, 503

– fretting damage, 452, 453

– non-damaging compressive loads, 504

– pin with flats, 505

– pin-loaded hole, 74, 76, 501

– plastic hole expansion, 506, 507

– split mandrel method, 507

– split sleeve method, 506

– size effect, 502

– stress concentration, 74

M

Mean stress sensitivity, 147–149, 152, 153

Miner rule, 297–316

- comparison of design options, 325
- comparison of load spectra severities, 325
- life estimates, 324
- relative Miner rule, 316
- shortcomings, 302–306
 - crack length at failure, 302
 - cycles below fatigue limit, 299, 312
 - notch root plasticity, 300
- $\Sigma n/N$ -values, 306, 551

Motor car, 264, 282, 401

N

Non-propagating crack, 22, 29

Notch effect:

- plastic zone at root of notch, 185
- prediction method of Kuhn and Hardrath, 178
- prediction method of Neuber, 177
- prediction method of Peterson, 176
- prediction method of Siebel, 180
- under combined loading, 190
- under cyclic torsion, 188

Notch geometry, 69

Notch root radius:

- effect of larger radius, 64
- sharp corner, 81

Notch sensitivity factor (q), 174

O

Omission of low-amplitude cycles, 290

Overload cycles (*see* Crack growth under VA loading)

P

Paris region, 223

Paris relation for the crack growth rate, 223

Part through cracks:

- break through, 249
- in laminates, 593, 594
- prediction on growth, 248
- stress intensity factor, 126

Peterson:

- book *Stress Concentration Factors*, 70
- prediction of notch effect, 176

Pin-loaded hole, 74, 76

Plane strain/plane stress:

- effect on crack closure, 230
- effect on crack tip displacements, 128, 129
- effect on crack tip plastic zone size, 130

Plastic hole expansion, 96, 507, 508

Plastic shake down, 166

Prediction of fatigue crack growth, 240

- crack driving force, 240
- crack growth resistance, 40
- effect of final crack length, 243, 546, 570–572
- effect of initial crack length, 241, 546, 571
- oblique crack front, 250, 251
- part through cracks, 248
 - break through, 249
 - semi-elliptical surface crack, 248
- through cracks, 243
 - crack growth in a lug, 244
 - crack growth in a stiffened panel, 247

Pressure vessel, 249, 261, 539, 552

P-S-N curves, 382

R

Random Gauss process, 277

Random load:

- broad band random load, 278
- crack growth under random loading, 345, 346
- narrow band random load, 278

Relative Miner rule, 316

Residual stress, 89

- built-in residual stress, 98
- elimination of residual stress, 102
- heat treatment, 97
- inhomogeneous plastic deformation, 93
- in surface layers, 424, 431
- introduced by production, 98
- measurements, 100
- Neuber postulate, 100
- residual stress at root of notch, 92, 93
- residual stresses in welds, 537, 538
- shot peening, 94, 431
- sources of residual stress, 91
- surface rolling, 433
- warpage 91, 94, 102

Riveted and bolted lap joints, 517

- different fasteners, 517
- eccentricity effect, 519

- effect of rivet squeeze force, 523
- prediction of fatigue life, 526
- secondary bending, 519
- Riveted and bolted symmetric joints, 508
 - clamping by bolts, 511
 - double strap joints, 508–510
- Run out, 145
- S**
- Safety (*see* Design procedures)
- Scatter, 373–394
 - case histories, 380
 - distribution function, 377
 - distribution of fatigue limit, 384, 386
 - distribution of fatigue strength, 382
 - normal (Gaussian) distribution, 377
 - Probit method, 383
 - scatter of crack growth, 388
 - scatter of crack initiation, 35, 36
 - scatter of structures, 389–392
 - scatter under VA-loading, 386
 - sources of scatter, 373
 - Staircase method, 384
 - Weibull distribution, 377
- Service-simulation fatigue test, 287
 - predictions based on service-simulation fatigue tests, 318
 - truncation effect, 321, 322
- Shear lips, 54, 342, 471
- Shear loading:
 - fatigue limit, 158
 - mean stress effect, 158
- Shot peening, 94, 431
- Similarity concept and fatigue cracks:
 - application to crack growth data, 136, 212
 - crack closure and the similarity concept, 228
 - crack growth predictions, 240
 - K -dominated zone, 131
 - material defect not similar to crack, 222
 - stress ratio effect on crack growth, 137
- Similarity concept and notch effect, 174
- Similitude (*see* Similarity)
- Size effect:
 - fatigue limit of notched specimens, 175
 - shape effect, 155
 - size effect of lug, 502
 - unnotched specimens, 153
- Slip band cracking, 19
- Small cracks:
 - crack growth barriers, 29
 - initial fast growth, 26
 - mechanically short cracks, 30
 - microcracks below fatigue limit, 30, 31
 - micro-structurally small cracks, 31
 - small cracks during major part of fatigue life, 143, 144
- Smith diagram, 148
- S-N curve, 144
 - Basquin relation, 144, 145, 204, CD-100
 - knee of S-N curve, 38, 44, 203, 204
 - notched specimens, 202
- Specimens:
 - central crack tension (CCT) specimen, 113
 - compact tension (CT) specimen, 121
 - different types, 397, 500
 - welded specimens, 540
- Spot welded joints, 555
- Stable tearing crack growth region, 224
- Strain energy release rate, 133–135
- Strain history life prediction model, 316
- Stress concentration factor:
 - calculation, 83–85, *see also* CD-94
 - central hole, 70
 - Heywood approximation, 70
 - definitions, 60
 - edge notch, 70
 - elliptical hole, 63, 64
 - fillet, 71
 - hole under shear load, 76, 77
 - lug, 75, 76
 - measurements, 82
 - shoulder notch, 73
 - T-head, 75
- Stress cycle definition, 142
- Stress gradient along notch surface, 68
- Stress intensity factor (K), 107
 - biaxial loading, 118, 119
 - central crack, 113
 - collinear cracks, 112
 - corner crack, 126
 - crack edge loading, 119
 - crack loaded by internal pressure, 123
 - crack opening, 127
 - curved crack front, 124
 - determination of K , 135
 - edge cracks, 115

- edge crack at hole, 116
- edge crack at notch, 115
- edge crack at window, 118
- elliptical crack, 126
- energy considerations, 133
- Feddersen equation, 114
- geometry factor, 112, 113
- K -dominated zone, 131
- mode I, II, III, 107
- part through crack, 108
- penny shaped crack, 125
- superposition, 122–124
- surface crack, 127
- through crack, 108
- Westergaard solution, 112
- Stress ratio, 142
- Stress relieving groove, 74, 513
- Stress severity factor, 530
- Stress-strain loop, 163
- Stress trajectories, 72
- Striations:
 - correspondence with cycles, 41
 - criterion for prediction, 362
 - striation forming, models, 42
 - to show delayed retardation, 340
- Superposition:
 - of crack loading cases, 122
 - of notch effects, 80, 81
- Surface effects on fatigue, 36–39, 421
 - on S-N curve, 38
 - variables, 36
- Surface phenomenon, 15–18
- Surface roughness reduction factor, 193–195
- Surface treatments, 421–436
 - subsurface cracking, 427
 - surface layers, 422
 - anodizing, 423
 - cladding layer, 423
 - induction hardening, 425
 - nitriding, 425
 - surface roughness, 428

T

- Tangential stress around hole, 65
- Temperature effects (*see* High and low

- temperature effects)
- Thickness effect on crack growth, 232
 - CA loading, 232
 - crack closure, 231, 335, 347
 - VA loading, 335, 347
- Threshold region, 218
 - crack growth below ΔK_{th} , 220
 - threshold ΔK (ΔK_{th}), 218
 - threshold experiments, 218, 219
- Torsion:
 - cyclic torsion fatigue, 47
 - notch effect under cyclic torsion, 188
 - spiral crack growth, 48
 - stress concentration in a shaft, 188–190
- Truncation of load spectrum:
 - fatigue crack growth, 349
 - fatigue life on notched specimens, 321, 322

V

- Variable-amplitude fatigue life (*see also* Sequence effects and Miner rule), 295–328
- Variable-amplitude fatigue life, 329–369

W

- Wave shape effect on fatigue crack growth:
 - effect of holding at S_{max} or S_{min} , 467–470
 - in corrosion fatigue, 466–467
- Welded joints, 535
 - crack growth life, 545
 - fatigue life under VA loading, 551
 - grinding of weld toe, 541
 - pressure vessel, 552
 - leak before break, 552, 553
 - reinforcement angle, 541
 - residual stresses in welds, 537, 538
 - S-N curves of classes of welded joints, 546, 547
 - S-N curves of welded specimens, 543
 - tubular offshore structure, 553
 - weld defects, 536–537
 - welded specimens, 540
 - welded structures, 539
 - worst case analysis, 546, 552
- Wöhler curve (*see* S-N curve)

imagine ...observe ... think

