



Abstract

This chapter covers concurrent programming. It introduces the concept of parallel computing and points out its importance. It compares sequential algorithms with parallel algorithms, and parallelism vs. concurrency. It explains the principles of threads and their advantages over processes. It covers threads operations in Pthreads by examples. These include threads management functions, threads synchronization tools of mutex, join, condition variables and barriers. It demonstrates concurrent programming using threads by detailed examples. These include matrix computation, quicksort and solving systems of linear equations by concurrent threads. It explains the deadlock problem and shows how to prevent deadlocks in concurrent programs. It covers semaphores and demonstrates their advantages over condition variables. It also explains the unique way of supporting threads in Linux. The programming project is to implement user-level threads. It presents a base system to help the reader get started. The base system supports dynamic creation, execution and termination of concurrent tasks, which are equivalent to threads executing in the same address space of a process. The project is for the reader to implement threads join, mutex and semaphores for threads synchronization and demonstrate their usage in concurrent programs. The programming project should allow the reader to have a deeper understanding of the principles and techniques of multitasking, threads synchronization and concurrent programming.

4.1 Introduction to Parallel Computing

In the early days, most computers have only one processing element, known as the processor or Central Processing Unit (CPU). Due to this hardware limitation, computer programs are traditionally written for serial computation. To solve a problem, a person would first design an algorithm, which describes how to solve the problem step by step, and then implement the algorithm by a computer program as a serial stream of instructions. With only a single CPU, both the individual instructions and the steps of an algorithm can only be executed sequentially one at a time. However, algorithms based on the principle of divide and conquer, e.g. binary search and quicksort, etc. often exhibit a high degree of parallelism, which can be exploited by using parallel or concurrent executions to speed up the computation. Parallel computing is a computing scheme which tries to use multiple processors executing parallel algorithms to solve problems faster. In the past, parallel computing is rarely

accessible to average programmers due to its extensive requirements of computing resources. With the advent of multicore processors in recent years, most operating systems, such as Linux, support Symmetrical Multiprocessing (SMP). Parallel computing has become a reality even for average programmers. The future of computing is clearly in the direction of parallel computing. It is imperative to introduce parallel computing to Computer Science and Computer Engineering students in an early stage. In this chapter, we shall cover the basic concepts and techniques of parallel computing through concurrent programming.

4.1.1 Sequential Algorithms vs. Parallel Algorithms

When describing sequential algorithms, a common way is to express the algorithm in a **begin-end** block, as show in the left-hand side of the following diagram.

```

--- Sequential Algorithm---|--- Parallel Algorithm ---
    begin                   |      cobegin
      step_1                 |      task_1
      step_2                 |      task_2
      . . .                 |      . . .
      step_n                 |      task_n
    end                     |      coend
  // next step             |      // next step
-----

```

The sequential algorithm inside the **begin-end** block may consist of many steps. All the steps are to be performed by a single task serially one step at a time. The algorithm ends when all the steps have completed. In contrast, the right-hand side of the diagram shows the description of a parallel algorithm, which uses a **cobegin-coend** block to specify separate tasks of a parallel algorithm. Within the **cobegin-coend** block, all tasks are to be performed in parallel. The next step following the **cobegin-coend** block will be performed only after all such tasks have completed.

4.1.2 Parallelism vs. Concurrency

In general, a parallel algorithm only identifies tasks that can be executed in parallel, but it does not specify how to map the tasks to processing elements. Ideally, all the tasks in a parallel algorithm should be executed simultaneously in real time. However, true parallel executions can only be achieved in systems with multiple processing elements, such as multiprocessor or multicore systems. On single CPU systems, only one task can execute at a time. In this case, different tasks can only execute concurrently, i.e. logically in parallel. In single CPU systems, concurrency is achieved through multitasking, which was covered in Chap. 3. We shall explain and demonstrate the principle and techniques of multitasking again in a programming project at the end of this chapter.

4.2 Threads

4.2.1 Principle of Threads

An operating system (OS) comprises many concurrent processes. In the process model, processes are independent execution units. Each process executes in either kernel mode or user mode. While in user mode, each process executes in a unique address space, which is separated from other processes. Although each process is an independent unit, it has only one execution path. Whenever a process must wait for something, e.g. an I/O completion event, it becomes suspended and the entire process execution stops. Threads are independent execution units in the same address space of a process. When creating a process, it is created in a unique address space with a main thread. When a process begins, it executes the main thread of the process. With only a main thread, there is virtually no difference between a process and a thread. However, the main thread may create other threads. Each thread may create yet more threads, etc. All threads in a process execute in the same address space of the process but each thread is an independent execution unit. In the threads model, if a thread becomes suspended, other threads may continue to execute. In addition to sharing a common address space, threads also share many other resources of a process, such as user id, opened file descriptors and signals, etc. A simple analogy is that a process is a house with a house master (the main thread). Threads are people living in the same house of a process. Each person in a house can carry on his/her activities independently, but they share some common facilities, such as the same mailbox, kitchen and bathroom, etc. Historically, most computer vendors used to support threads in their own proprietary operating systems. The implementations vary considerably from system to system. Currently, almost all OS support Pthreads, which is the threads standard of IEEE POSIX 1003.1c (POSIX 1995). For more information, the reader may consult numerous books (Buttlar et al. 1996) and online articles on Pthreads programming (Pthreads 2017).

4.2.2 Advantages of Threads

Threads have many advantages over processes.

- (1). **Thread creation and switching are faster:** The context of a process is complex and large. The complexity stems mainly from the need for managing the process image. For example, in a system with virtual memory, a process image may be composed of many units of memory called **pages**. During execution some of the pages are in memory while others may not. The OS kernel must use several page tables and many levels of hardware assistances to keep track of the pages of each process. To create a new process, the OS must allocate memory and build the page tables for the process. To create a thread within a process, the OS does not have to allocate memory and build page tables for the new thread since it shares the same address space of the process. So, creating a thread is faster than creating a process. Also, thread switching is faster than process switching for the following reasons. Process switching involves replacing the complex paging environment of one process with that of another, which requires a lot of operations and time. In contrast, switching among threads in the same process is much simpler and faster because the OS kernel only needs to switch the execution points without changing the process image.
- (2). **Threads are more responsive:** A process has only a single execution path. When a process becomes suspended, the entire process execution stops. In contrast, when a thread becomes suspended, other threads in the same process can continue to execute. This allows a program

with threads to be more responsive. For example, in a process with multiple threads, while one thread becomes blocked to wait for I/O, other threads can still do computations in the background. In a server with threads, the server can serve multiple clients concurrently.

- (3). **Threads are better suited to parallel computing:** The goal of parallel computing is to use multiple execution paths to solve problems faster. Algorithms based on the principle of divide and conquer, e.g. binary search and quicksort, etc. often exhibit a high degree of parallelism, which can be exploited by using parallel or concurrent executions to speed up the computation. Such algorithms often require the execution entities to share common data. In the process model, processes cannot share data efficiently because their address spaces are all distinct. To remedy this problem, processes must use **Interprocess Communication (IPC)** to exchange data or some other means to include a common data area in their address spaces. In contrast, threads in the same process share all the (global) data in the same address space. Thus, writing programs for parallel executions using threads is simpler and more natural than using processes.

4.2.3 Disadvantages of Threads

On the other hand, threads also have some disadvantages, which include

- (1). Because of shared address space, threads needs explicit synchronization from the user.
- (2). Many library functions may not be threads safe, e.g. the traditional strtok() function, which divides a string into tokens in-line. In general, any function which uses global variables or relies on contents of static memory is not threads safe. Considerable efforts are needed to adapt library functions to the threads environment.
- (3). On single CPU systems, using threads to solve problems is actually slower than using a sequential program due to the overhead in threads creation and context switching at run-time.

4.3 Threads Operations

The execution locus of a thread is similar to that a process. A thread can execute in either kernel mode or user mode. While in user mode, threads executes in the same address space of a process but each has its own execution stack. As an independent execution unit, a thread can make system calls to the OS kernel, subject to the kernel's scheduling policy, becomes suspended, activated to resume execution, etc. To take advantage of the shared address space of threads, the OS kernel's scheduling policy may favor threads of the same process over those in different processes. As of now, almost all operating systems support POSIX Pthreads, which defines a standard set of Application Programming Interfaces (APIs) to support threads programming. In the following, we shall discuss and demonstrate concurrent programming by Pthreads in Linux (Goldt et al 1995; IBM; Love 2005; Linux Man Page Project 2017).

4.4 Threads Management Functions

The Pthreads library offers the following APIs for threads management.

```
pthread_create(thread, attr, function, arg): create thread
pthread_exit(status) : terminate thread
```

```
pthread_cancel(thread)    : cancel thread
pthread_attr_init(attr)  : initialize thread attributes
pthread_attr_destroy(attr): destroy thread attribute
```

4.4.1 Create Thread

threads are created by the `pthread_create()` function.

```
int pthread_create (pthread_t *pthread_id, pthread_attr_t *attr,
                  void *(*func)(void *), void *arg);
```

which returns 0 on success or an error number on failure. Parameters to the `pthread_create()` function are

.pthread_id is a pointer to a variable of the `pthread_t` type. It will be filled with the unique thread ID assigned by the OS kernel. In POSIX, `pthread_t` is an opaque type. The programmer should not know the contents of an opaque object because it may depend on implementation. A thread may get its own ID by the `pthread_self()` function. In Linux, `pthread_t` type is defined as **unsigned long**, so thread ID can be printed as `%lu`.

.attr is a pointer to another opaque data type, which specifies the thread attributes, which are explained in more detail below.

.func is the entry address of a function for the new thread to execute.

.arg is a pointer to a parameter for the thread function, which can be written as

```
void *func(void *arg)
```

Among these, the `attr` parameter is the most complex one. The steps of using an `attr` parameter are as follows.

- (1). Define a pthread attribute variable `pthread_attr_t attr`
- (2). Initialize the attribute variable with `pthread_attr_init(&attr)`
- (3). Set the attribute variable and use it in `pthread_create()` call
- (4). If desired, free the `attr` resource by `pthread_attr_destroy(&attr)`

The following shows some examples of using the attribute parameter. By default, every thread is created to be joinable with other threads. If desired, a thread can be created with the detached attribute, which makes it non-joinable with other threads. The following code segment shows how to create a detached thread.

```
pthread_attr_t attr;           // define an attr variable
pthread_attr_init(&attr);     // initialize attr
pthread_attr_setdetachstate(&attr, PTHREAD_CREATE_DETACHED); // set attr
pthread_create(&thread_id, &attr, func, NULL); // create thread with attr
pthread_attr_destroy(&attr);  // optional: destroy attr
```

Every thread is created with a default stack size. During execution, a thread may find out its stack size by the function

```
size_t pthread_attr_getstacksize()
```

which returns the default stack size. The following code segment shows how to create a thread with a specific stack size.

```
pthread_attr_t attr;           // attr variable
size_t stacksize;            // stack size
pthread_attr_init(&attr);     // initialize attr
stacksize = 0x10000;         // stacksize=16KB;
pthread_attr_setstacksize (&attr, stacksize); // set stack size in attr
pthread_create(&threads[t], &attr, func, NULL); // create thread with stack
                                                    size
```

If the attr parameter is NULL, threads will be created with default attributes. In fact, this is the recommended way of creating threads, which should be followed unless there is a compelling reason to alter the thread attributes. In the following, we shall always use the default attributes by setting attr to NULL.

4.4.2 Thread ID

Thread ID is an opaque data type, which depends on implementation. Therefore, thread IDs should not be compared directly. If needed, they can be compared by the `pthread_equal()` function.

```
int pthread_equal (pthread_t t1, pthread_t t2);
```

which returns zero if the threads are different threads, non-zero otherwise.

4.4.3 Thread Termination

A thread terminates when the thread function finishes. Alternatively, a thread may call the function

```
int pthread_exit (void *status);
```

to terminate explicitly, where status is the exit status of the thread. As usual, a 0 exit value means normal termination, and non-zero values mean abnormal termination.

4.4.4 Thread Join

A thread can wait for the termination of another thread by

```
int pthread_join (pthread_t thread, void **status_ptr);
```

The exit status of the terminated thread is returned in status_ptr.

4.5 Threads Example Programs

4.5.1 Sum of Matrix by Threads

Example 4.1: Assume that we want to compute the sum of all the elements in an $N \times N$ matrix of integers. The problem can be solved by a concurrent algorithm using threads. In this example, the main thread first generates an $N \times N$ matrix of integers. Then it creates N working threads, passing as parameter a unique row number to each working thread, and waits for all the working threads to terminate. Each working thread computes the partial sum of a distinct row, and deposits the partial sum in a corresponding row of a global array `int sum[N]`. When all the working threads have finished, the main thread resumes. It computes the total sum by adding the partial sums generated by the working threads. The following shows the complete C code of the example program C4.1. Under Linux, the program must be compiled as

```
gcc C4.1.c -pthread
```

```

**** C4.1.c file: compute matrix sum by threads ***
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#define N 4
int A[N][N], sum[N];

void *func(void *arg)          // threads function
{
    int j, row;
    pthread_t tid = pthread_self(); // get thread ID number
    row = (int)arg;                // get row number from arg
    printf("Thread %d [%lu] computes sum of row %d\n", row, tid, row);
    for (j=0; j<N; j++)           // compute sum of A[row] in global sum[row]
        sum[row] += A[row][j];
    printf("Thread %d [%lu] done: sum[%d] = %d\n",
           row, tid, row, sum[row]);
    pthread_exit((void*)0); // thread exit: 0=normal termination
}

int main (int argc, char *argv[])
{
    pthread_t thread[N];          // thread IDs
    int i, j, r, total = 0;
    void *status;
    printf("Main: initialize A matrix\n");
    for (i=0; i<N; i++){
        sum[i] = 0;
        for (j=0; j<N; j++){
            A[i][j] = i*N + j + 1;
            printf("%4d ", A[i][j]);
        }
        printf("\n");
    }
}

```

```

}
printf("Main: create %d threads\n", N);
for(i=0; i<N; i++) {
    pthread_create(&thread[i], NULL, func, (void *)i);
}
printf("Main: try to join with threads\n");
for(i=0; i<N; i++) {
    pthread_join(thread[i], &status);
    printf("Main: joined with %d [%lu]: status=%d\n",
           i, thread[i], (int)status);
}
printf("Main: compute and print total sum: ");
for (i=0; i<N; i++)
    total += sum[i];
printf("total = %d\n", total);
pthread_exit(NULL);
}

```

Figure 4.1 shows the outputs of running the Example Program C4.1. It shows the executions of individual threads and their computed partial sums. It also demonstrates the thread join operation.

4.5.2 Quicksort by Threads

Example 4.2: Quicksort by Concurrent Threads

In this example, we shall implement a parallel quicksort program by threads. When the program starts, it runs as the main thread of a process. The main thread calls `qsort(&arg)`, with `arg = [lowerbound=0, upperbound=N-1]`. The `qsort()` function implements quicksort of an array of `N` integers. In `qsort()`, the thread picks a pivot element to divide the array into two parts such that all elements in the left part are less than the pivot and all elements in the right part are greater than the

```

Main: initialize A matrix
 1  2  3  4
 5  6  7  8
 9 10 11 12
13 14 15 16
Main: create 4 threads
Thread 0 [3075390272] computes sum of row 0
Thread 0 [3075390272] done: sum[0] = 10
Thread 3 [3050212160] computes sum of row 3
Thread 3 [3050212160] done: sum[3] = 58
Thread 2 [3058604864] computes sum of row 2
Thread 2 [3058604864] done: sum[2] = 42
Thread 1 [3066997568] computes sum of row 1
Main: try to join with threads
Thread 1 [3066997568] done: sum[1] = 26
Main: joined with 0 [3075390272]: status=0
Main: joined with 1 [3066997568]: status=0
Main: joined with 2 [3058604864]: status=0
Main: joined with 3 [3050212160]: status=0
Main: compute and print total sum: total = 136

```

Fig. 4.1 Sample Outputs of Example 4.1

pivot. Then it creates two subthreads to sort each of the two parts, and waits for the subthreads to finish. Each subthread sorts its own range by the same algorithm recursively. When all the subthreads have finished, the main thread resumes. It prints the sorted array and terminates. As is well known, the number of sorting steps of quicksort depends on the order of the unsorted data, which affects the number of threads needed in the qsort program.

```

/***** C4.2.c: quicksort by threads *****/
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

typedef struct{
    int upperbound;
    int lowerbound;
}PARM;

#define N 10
int A[N] = {5,1,6,4,7,2,9,8,0,3}; // unsorted data

int print() // print current a[] contents
{
    int i;
    printf("[ ");
    for (i=0; i<N; i++)
        printf("%d ", a[i]);
    printf("]\n");
}

void *qsort(void *aptr)
{
    PARM *ap, aleft, aright;
    int pivot, pivotIndex, left, right, temp;
    int upperbound, lowerbound;

    pthread_t me, leftThread, rightThread;
    me = pthread_self();
    ap = (PARM *)aptr;
    upperbound = ap->upperbound;
    lowerbound = ap->lowerbound;
    pivot = a[upperbound]; // pick low pivot value
    left = lowerbound - 1; // scan index from left side
    right = upperbound; // scan index from right side
    if (lowerbound >= upperbound)
        pthread_exit(NULL);

    while (left < right) { // partition loop
        do { left++; } while (a[left] < pivot);
        do { right--; } while (a[right] > pivot);
        if (left < right) {

```

```

        temp = a[left];
        a[left] = a[right];
        a[right] = temp;
    }
}
print();
pivotIndex = left;          // put pivot back
temp = a[pivotIndex];
a[pivotIndex] = pivot;
a[upperbound] = temp;
// start the "recursive threads"
aleft.upperbound = pivotIndex - 1;
aleft.lowerbound = lowerbound;
aright.upperbound = upperbound;
aright.lowerbound = pivotIndex + 1;
printf("%lu: create left and right threads\n", me);
pthread_create(&leftThread, NULL, qsort, (void *)&aleft);
pthread_create(&rightThread, NULL, qsort, (void *)&aright);
// wait for left and right threads to finish
pthread_join(leftThread, NULL);
pthread_join(rightThread, NULL);
printf("%lu: joined with left & right threads\n", me);
}

int main(int argc, char *argv[])
{
    PARM arg;
    int i, *array;
    pthread_t me, thread;
    me = pthread_self();
    printf("main %lu: unsorted array = ", me);
    print();
    arg.upperbound = N-1;
    arg.lowerbound = 0;
    printf("main %lu create a thread to do QS\n", me);
    pthread_create(&thread, NULL, qsort, (void *)&arg);
    // wait for QS thread to finish
    pthread_join(thread, NULL);
    printf("main %lu sorted array = ", me);
    print();
}

```

Figure 4.2 shows the outputs of running the Example Program C4.2, which demonstrates parallel quicksort by concurrent threads.

```

main 3075553024: unsorted array = [ 5 1 6 4 7 2 9 8 0 3 ]
main 3075553024 create a thread to do QS
[ 0 1 2 4 7 6 9 8 5 3 ]
3075550016: create left and right threads
[ 0 1 2 3 7 6 9 8 5 4 ]
3067157312: create left and right threads
[ 0 1 2 3 7 6 9 8 5 4 ]
3057646400: create left and right threads
[ 0 1 2 3 4 6 9 8 5 7 ]
3049253696: create left and right threads
[ 0 1 2 3 4 6 5 8 9 7 ]
3003116352: create left and right threads
[ 0 1 2 3 4 6 5 7 9 8 ]
2986330944: create left and right threads
[ 0 1 2 3 4 6 5 7 8 9 ]
2994723648: create left and right threads
3049253696: joined with left & right threads
3067157312: joined with left & right threads
2986330944: joined with left & right threads
2994723648: joined with left & right threads
3003116352: joined with left & right threads
3057646400: joined with left & right threads
3075550016: joined with left & right threads
main 3075553024 sorted array = [ 0 1 2 3 4 5 6 7 8 9 ]

```

Fig. 4.2 Outputs of Parallel Quicksort Program

4.6 Threads Synchronization

Since threads execute in the same address space of a process, they share all the global variables and data structures in the same address space. When several threads try to modify the same shared variable or data structure, if the outcome depends on the execution order of the threads, it is called a **race condition**. In concurrent programs, race conditions must not exist. Otherwise, the results may be inconsistent. In addition to the join operation, concurrently executing threads often need to cooperate with one another. In order to prevent race conditions, as well as to support threads cooperation, threads need synchronization. In general, synchronization refers to the mechanisms and rules used to ensure the integrity of shared data objects and coordination of concurrently executing entities. It can be applied to either processes in kernel mode or threads in user mode. In the following, we shall discuss the specific problem of threads synchronization in Pthreads.

4.6.1 Mutex Locks

The simplest kind of synchronizing tool is a lock, which allows an execution entity to proceed only if it possesses the lock. In Pthreads, locks are called **mutex**, which stands for **Mutual Exclusion**. Mutex variables are declared with the type `pthread_mutex_t`, and they must be initialized before using. There are two ways to initialize a mutex variable.

(1) Statically, as in

```
pthread_mutex_t m = PTHREAD_MUTEX_INITIALIZER;
```

which defines a mutex variable `m` and initializes it with default attributes.

- (2) Dynamically with the `pthread_mutex_init()` function, which allows setting the mutex attributes by an `attr` parameter, as in

```
pthread_mutex_init (pthread_mutex_t *m, pthread_mutexattr_t, *attr);
```

As usual, the `attr` parameter can be set to `NULL` for default attributes.

After initialization, mutex variables can be used by threads via the following functions.

```
int pthread_mutex_lock (pthread_mutex_t *m);    // lock mutex
int pthread_mutex_unlock (pthread_mutex_t *m);  // unlock mutex
int pthread_mutex_trylock (pthread_mutex_t *m); // try to lock mutex
int pthread_mutex_destroy (pthread_mutex_t *m); // destroy mutex
```

Threads use mutexes as locks to protect shared data objects. A typical usage of mutex is as follows. A thread first creates a mutex and initializes it once. A newly created mutex is in the unlocked state and without an owner. Each thread tries to access a shared data object by

```
pthread_mutex_lock(&m);    // lock mutex
    access shared data object; // access shared data in a critical region
pthread_mutex_unlock(&m); // unlock mutex
```

When a thread executes `pthread_mutex_lock(&m)`, if the mutex is unlocked, it locks the mutex, becomes the mutex owner and continues. Otherwise, it becomes blocked and waits in the mutex waiting queue. Only the thread which has acquired the mutex lock can access the shared data object. A sequence of executions which can only be performed by one execution entity at a time is commonly known as a **Critical Region (CR)**. In Pthreads, mutexes are used as locks to protect Critical Regions to ensure at most one thread can be inside a CR at any time. When the thread finishes with the shared data object, it exits the CR by calling `pthread_mutex_unlock(&m)` to unlock the mutex. A locked mutex can only be unlocked by the current owner. When unlocking a mutex, if there are no blocked threads in the mutex waiting queue, it unlocks the mutex and the mutex has no owner. Otherwise, it unblocks a waiting thread from the mutex waiting queue, which becomes the new owner, and the mutex remains locked. When all the threads are finished, the mutex may be destroyed if it was dynamically allocated. We demonstrate threads synchronization using mutex lock by an example.

Example 4.3: This example is a modified version of Example 4.1. As before, we shall use N working threads to compute the sum of all the elements of an $N \times N$ matrix of integers. Each working thread computes the partial sum of a row. Instead of depositing the partial sums in a global `sum[]` array, each working thread tries to update a global variable, `total`, by adding its partial sum to it. Since all the working threads try to update the same global variable, they must be synchronized to prevent race conditions. This can be achieved by a mutex lock, which ensures that only one working thread can update the `total` variable at a time in a Critical Region. The following shows the Example Program C4.3.

```
/** C4.3.c: matrix sum by threads with mutex lock */
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
```

```

#define N 4
int A[N][N];

int total = 0;           // global total
pthread_mutex_t *m;     // mutex pointer
void *func(void *arg)   // working thread function
{
    int i, row, sum = 0;
    pthread_t tid = pthread_self(); // get thread ID number
    row = (int)arg;           // get row number from arg
    printf("Thread %d [%lu] computes sum of row %d\n", row, tid, row);
    for (i=0; i<N; i++)      // compute partial sum of A[row] in
        sum += A[row][i];
    printf("Thread %d [%lu] update total with %d : ", row, tid, sum);
    pthread_mutex_lock(m);
    total += sum;           // update global total inside a CR
    pthread_mutex_unlock(m);
    printf("total = %d\n", total);
}

int main (int argc, char *argv[])
{
    pthread_t thread[N];
    int i, j, r;
    void *status;
    printf("Main: initialize A matrix\n");
    for (i=0; i<N; i++){
        sum[i] = 0;
        for (j=0; j<N; j++){
            A[i][j] = i*N + j + 1;
            printf("%4d ", A[i][j]);
        }
        printf("\n");
    }
    // create a mutex m
    m = (pthread_mutex_t *)malloc(sizeof(pthread_mutex_t));
    pthread_mutex_init(m, NULL); // initialize mutex m
    printf("Main: create %d threads\n", N);
    for(i=0; i<N; i++) {
        pthread_create(&thread[i], NULL, func, (void *)i);
    }
    printf("Main: try to join with threads\n");
    for(i=0; i<N; i++) {
        pthread_join(thread[i], &status);
        printf("Main: joined with %d [%lu]: status=%d\n",
            i, thread[i], (int)status);
    }
    printf("Main: total = %d\n", total);
    pthread_mutex_destroy(m); // destroy mutex m
    pthread_exit(NULL);
}

```

```

Main: initialize A matrix
  1  2  3  4
  5  6  7  8
  9 10 11 12
 13 14 15 16
Main: create thread 0
Main: create thread 1
Main: create thread 2
Thread 0 [3076299584] computes sum of row 0
thread 0 [3076299584] update total with 10 : Thread 0: total = 10
Main: create thread 3
Thread 1 [3067906880] computes sum of row 1
thread 1 [3067906880] update total with 26 : Thread 1: total = 36
Thread 2 [3059514176] computes sum of row 2
thread 2 [3059514176] update total with 42 : Thread 2: total = 78
Thread 3 [3051019072] computes sum of row 3
thread 3 [3051019072] update total with 58 : Thread 3: total = 136
Main: joined with 0 [3076299584]: status=0
Main: joined with 1 [3067906880]: status=0
Main: joined with 2 [3059514176]: status=0
Main: joined with 3 [3051019072]: status=0
Main: total = 136

```

Fig. 4.3 Outputs of Example 4.3 Program

Figure 4.3 show the sample outputs of running the Example 4.3 program, which demonstrates mutex lock in Pthreads.

4.6.2 Deadlock Prevention

Mutexes use the locking protocol. If a thread can not acquire a mutex lock, it becomes blocked, waiting for the mutex to be unlocked before continuing. In any locking protocol, misuse of locks may lead to problems. The most well-known and prominent problem is deadlock. **Deadlock** is a condition, in which many execution entities mutually wait for one another so that none of them can proceed. To illustrate this, assume that a thread T1 has acquired a mutex lock m1 and tries to lock another mutex m2. Another thread T2 has acquired the mutex lock m2 and tries to lock the mutex m1, as shown in the following diagram.

Thread T1:	Thread T2:
lock(m1);	lock(m2);
.
lock(m2);	lock(m1);

In this case, T1 and T2 would mutually wait for each other forever, so they are in a deadlock due to crossed locking requests. Similar to no race conditions, deadlocks must not exist in concurrent programs. There are many ways to deal with possible deadlocks, which include **deadlock prevention**, deadlock avoidance, deadlock detection and recovery, etc. In real systems, the only practical way is deadlock prevention, which tries to prevent deadlocks from occurring when designing parallel algorithms. A simple way to prevent deadlock is to order the mutexes and ensure that every thread requests mutex locks only in a single direction, so that there are no loops in the request sequences.

However, it may not be possible to design every parallel algorithm with only uni-directional locking requests. In such cases, the conditional locking function, `pthread_mutex_trylock()`, may be used to prevent deadlocks. The `trylock()` function returns immediately with an error if the mutex is already locked. In that case, the calling thread may back-off by releasing some of the locks it already holds, allowing other threads to continue. In the above crossed locking example, we may redesign one of the threads, e.g. T1, as follows, which uses conditional locking and back-off to prevent the deadlock.

Thread T1:

```

-----
while(1){
    lock(m1);
    if (!trylock(m2)) // if trylock m2 fails
        unlock(m1); // back-off and retry
    else
        break;
    // delay some random time before retry
}
-----

```

4.6.3 Condition Variables

Mutexes are used only as locks, which ensure threads to access shared data objects exclusively in Critical Regions. Condition variables provide a means for threads cooperation. Condition variables are always used in conjunction with mutex locks. This is no surprise because mutual exclusion is the basis of all synchronizing mechanisms. In Pthreads, condition variables are declared with the type `pthread_cond_t`, and must be initialized before using. Like mutexes, condition variables can also be initialized in two ways.

- (1) Statically, when it is declared, as in

```
pthread_cond_t con = PTHREAD_COND_INITIALIZER;
```

which defines a condition variable, `con`, and initializes it with default attributes.

- (2) Dynamically with the `pthread_cond_init()` function, which allows setting a condition variable with an `attr` parameter. For simplicity, we shall always use a `NULL` `attr` parameter for default attributes.

The following code segments show how to define a condition variable with an associated mutex lock.

```

pthread_mutex_t con_mutex; // mutex for a condition variable
pthread_cond_t con; // a condition variable that relies on con_mutex
pthread_mutex_init(&con_mutex, NULL); // initialize mutex
pthread_cond_init(&con, NULL); // initialize con

```

When using a condition variable, a thread must acquire the associated mutex lock first. Then it performs operations within the Critical Region of the mutex lock and releases the mutex lock, as in

```
pthread_mutex_lock(&con_mutex);
    modify or test shared data objects
    use condition variable con to wait or signal conditions
pthread_mutex_unlock(&con_mutex);
```

Within the CR of the mutex lock, threads may use condition variables to cooperate with one another via the following functions.

pthread_cond_wait(condition, mutex): This function blocks the calling thread until the specified condition is signaled. This routine should be called while mutex is locked. It will automatically release the mutex lock while the thread waits. After signal is received and a blocked thread is awakened, mutex will be automatically locked.

pthread_cond_signal(condition): This function is used to signal, i.e. to wake up or unblock, a thread which is waiting on the condition variable. It should be called after mutex is locked, and must unlock mutex in order for **pthread_cond_wait()** to complete.

pthread_cond_broadcast(condition): This function unblocks all threads that are blocked on the condition variable. All unblocked threads will compete for the same mutex to access the condition variable. Their order of execution depends on threads scheduling.

We demonstrate thread cooperation using condition variables by an example.

4.6.4 Producer-Consumer Problem

Example 4.4: In this example, we shall implement a simplified version of the **producer-consumer problem**, which is also known as the **bounded buffer** problem, using threads and condition variables. The producer-consumer problem is usually defined with processes as executing entities, which can be regarded as threads in the current context. The problem is defined as follows.

A set of producer and consumer processes share a finite number of buffers. Each buffer contains a unique item at a time. Initially, all the buffers are empty. When a producer puts an item into an empty buffer, the buffer becomes full. When a consumer gets an item from a full buffer, the buffer becomes empty, etc. A producer must wait if there are no empty buffers. Similarly, a consumer must wait if there are no full buffers. Furthermore, waiting processes must be allowed to continue when their awaited events occur.

In the example program, we shall assume that each buffer holds an integer value. The shared global variables are defined as

```
// shared global variables
int buf[NBUF];           // circular buffers
int head, tail;       // indices
int data;             // number of full buffers
```

The buffers are used as a set of circular buffers. The index variables **head** is for putting an item into an empty buffer, and **tail** is for taking an item out of a full buffer. The variable **data** is the number of full buffers. To support cooperation between producer and consumer, we define a mutex and two condition variables.

```
pthread_mutex_t mutex;      // mutex lock
pthread_cond_t empty, full; // condition variables
```

where **empty** represents the condition of any empty buffers, and **full** represents the condition of any full buffers. When a producer finds there are no empty buffers, it waits on the **empty** condition variable, which is signaled whenever a consumer has consumed a full buffer. Likewise, when a consumer finds there are no full buffers, it waits on the **full** condition variable, which is signaled whenever a producer puts an item into an empty buffer.

The program starts with the main thread, which initializes the buffer control variables and the condition variables. After initialization, it creates a producer and a consumer thread and waits for the threads to join. The buffer size is set to NBUF=5 but the producer tries to put N=10 items into the buffer area, which would cause it to wait when all the buffers are full. Similarly, the consumer tries to get N=10 items from the buffers, which would cause it to wait when all the buffers are empty. In either case, a waiting thread is signaled up by another thread when the awaited conditions are met. Thus, the two threads cooperate with each other through the condition variables. The following shows the program code of Example Program C4.4, which implements a simplified version of the producer-consumer problem with only one producer and one consumer.

```
/* C4.4.c: producer-consumer by threads with condition variables */
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

#define NBUF      5
#define N         10

// shared global variables
int buf[NBUF];      // circular buffers
int head, tail;     // indices
int data;           // number of full buffers
pthread_mutex_t mutex; // mutex lock
pthread_cond_t empty, full; // condition variables

int init()
{
    head = tail = data = 0;
    pthread_mutex_init(&mutex, NULL);
    pthread_cond_init(&fullBuf, NULL);
    pthread_cond_init(&emptyBuf, NULL);
}

void *producer()
{
    int i;
    pthread_t me = pthread_self();
    for (i=0; i<N; i++){ // try to put N items into buf[ ]
        pthread_mutex_lock(&mutex); // lock mutex
        if (data == NBUF){
            printf ("producer %lu: all bufs FULL: wait\n", me);
```

```

        pthread_cond_wait(&empty, &mutex); // wait
    }
    buf[head++] = i+1;                // item = 1,2,..,N
    head %= NBUF;                    // circular bufs
    data++;                          // inc data by 1
    printf("producer %lu: data=%d value=%d\n", me, bp->data, i+1);
    pthread_mutex_unlock(&mutex);    // unlock mutex
    pthread_cond_signal(&full);      // unblock a consumer, if any
}
printf("producer %lu: exit\n", me);
}

void *consumer()
{
    int i, c;
    pthread_t me = pthread_self();
    for (i=0; i<N; i++) {
        pthread_mutex_lock(&mutex);    // lock mutex
        if (data == 0) {
            printf ("consumer %lu: all bufs EMPTY: wait\n", me);
            pthread_cond_wait(&full, &mutex); // wait
        }
        c = buf[tail++];                // get an item
        tail %= NBUF;
        data--;                        // dec data by 1
        printf("consumer %lu: value=%d\n", me, c);
        pthread_mutex_unlock(&mutex);    // unlock mutex
        pthread_cond_signal(&empty);      // unblock a producer, if any
    }
    printf("consumer %lu: exit\n", me);
}

int main ()
{
    pthread_t pro, con;
    init();
    printf("main: create producer and consumer threads\n");
    pthread_create(&pro, NULL, producer, NULL);
    pthread_create(&con, NULL, consumer, NULL);
    printf("main: join with threads\n");
    pthread_join(pro, NULL);
    pthread_join(con, NULL);
    printf("main: exit\n");
}

```

Figure 4.4 shows the output of running the producer-consumer example program.

```

main: create producer and consumer threads
main: join with threads
producer 3076275008: data=1 value=1
producer 3076275008: data=2 value=2
producer 3076275008: data=3 value=3
producer 3076275008: data=4 value=4
producer 3076275008: data=5 value=5
producer 3076275008: all bufs FULL: wait
consumer 3067882304: value=1
consumer 3067882304: value=2
consumer 3067882304: value=3
consumer 3067882304: value=4
consumer 3067882304: value=5
consumer 3067882304: all bufs EMPTY: wait
producer 3076275008: data=1 value=6
producer 3076275008: data=2 value=7
producer 3076275008: data=3 value=8
producer 3076275008: data=4 value=9
consumer 3067882304: value=6
consumer 3067882304: value=7
consumer 3067882304: value=8
consumer 3067882304: value=9
consumer 3067882304: all bufs EMPTY: wait
producer 3076275008: data=1 value=10
producer 3076275008: exit
consumer 3067882304: value=10
consumer 3067882304: exit
main: exit

```

Fig. 4.4 Outputs of Producer-Consumer Program

4.6.5 Semaphores

Semaphores are general mechanisms for process synchronization. A (counting) semaphore is a data structure

```

struct sem{
    int value;           // semaphore (counter) value;
    struct process *queue // a queue of blocked processes
};

```

Before using, a semaphore must be initialized with an initial value and an empty waiting queue. Regardless of the hardware platform, i.e. whether on single CPU systems or multiprocessing systems, the low level implementation of semaphores guarantees that each semaphore can only be operated by one executing entity at a time and operations on semaphores are **atomic** (indivisible) or **primitive** from the viewpoint of executing entities. The reader may ignore such details here and focus on the high level operations on semaphores and their usage as a mechanism for process synchronization. The most well-known operations on semaphores are P and V (Dijkstra 1965), which are defined as follows.

```

-----
P(struct semaphore *s) | V(struct semaphore *s)
{                       | {
    s->value--;          |     s->value++;
    if (s->value < 0)    |     if (s->value <= 0)
        BLOCK(s);       |         SIGNAL(s);
}                       | }
-----

```

where BLOCK(s) blocks the calling process in the semaphore's waiting queue, and SIGNAL (s) unblocks a process from the semaphore's waiting queue.

Semaphores are not part of the original Pthreads standard. However, most Pthreads now support semaphores of POSIX 1003.1b. POSIX semaphores include the following functions

```
int sem_init(sem, value) : initialize sem with an initial value
int sem_wait(sem)       : similar to P(sem)
int sem_post(sem)       : similar to V(sem)
```

The major difference between semaphores and condition variables is that the former includes a counter, manipulate the counter, test the counter value to make decisions, etc. all in the Critical Region of atomic or primitive operations, whereas the latter requires a specific mutex lock to enforce the Critical Region. In Pthreads, mutexes are strictly for locking and condition variables are for threads cooperation. In contrast, counting semaphores with initial value 1 can be used as locks. Semaphores with other initial values can be used for cooperation. Therefore, semaphores are more general and flexible than condition variables. The following example illustrates the advantages of semaphores over condition variables.

Example 4.5: The producer-consumer problem can be solved more efficiently by using semaphores. In this example, **empty=N** and **full=0** are semaphores for producers and consumers to cooperate with one another, and **mutex=1** is a lock semaphore for processes to access shared buffers one at a time in a Critical Region. The following shows the pseudo code of the producer-consumer problem using semaphores.

```
ITEM buf[N];           // N buffers of ITEM type
int head=0, tail=0;   // buffer indices
struct semaphore empty=N, full=0, mutex=1; // semaphores

----- Producer ----- Consumer-----
while(1){              | while(1){
  produce an item;     |   ITEM item;
  P(&empty);            |   P(&full);
  P(&mutex);            |   P(&mutex)
  buf[head++]=item;    |   item=buf[tail++];
  head %= N;           |   tail %= N;
  V(&mutex);           |   V(&mutex);
  V(&full);            |   V(&empty);
}                      | }
```

4.6.6 Barriers

The threads join operation allows a thread (usually the main thread) to wait for the termination of other threads. After all awaited threads have terminated, the main thread may create new threads to continue executing the next parts of a parallel program. This requires the overhead of creating new threads. There are situations in which it would be better to keep the threads alive but require them not to go on until all of them have reached a prescribed point of synchronization. In Pthreads, the mechanism is the **barrier**, along with a set of barrier functions. First, the main thread creates a barrier object

```
pthread_barrier_t barrier;
```

and calls

```
pthread_barrier_init(&barrier, NULL, nthreads);
```

to initialize it with the number of threads that are to be synchronized at the barrier. Then the main thread creates working threads to perform tasks. The working threads use

```
pthread_barrier_wait( &barrier)
```

to wait at the barrier until the specified number of threads have reached the barrier. When the last thread arrives at the barrier, all the threads resume execution again. In this case, a barrier acts as a rendezvous point, rather than as a graveyard, of threads. We illustrate the use of barriers by an example.

4.6.7 Solve System of Linear Equations by Concurrent Threads

We demonstrate applications of concurrent threads and threads join and barrier operations by an example.

Example 4.6: The example is to solve a system of linear equations by concurrent threads. Assume $AX = B$ is a system of linear equations, where A is an $N \times N$ matrix of real numbers, X is a column vector of N unknowns and B is column vector of constants. The problem is to compute the solution vector X . The most well known algorithm for solving systems of linear equations is **Gauss elimination**. The algorithm consists of 2 major steps; **row reduction**, which reduces the combined matrix $[A|B]$ to an upper-triangular form, followed by **back substitution**, which computes the solution vector X . In the row-reduction steps, **partial pivoting** is a scheme which ensures the leading element of the row used to reduce other rows has the maximum absolute value. Partial pivoting helps improve the accuracy of the numerical computations. The following shows a Gauss elimination algorithm with partial pivoting.

/****** Gauss Elimination Algorithm with Partial Pivoting *****/

Step 1: Row reduction: reduce $[A|B]$ to upper triangular form

```
for (i=0; i<N ; i++){          // for rows i = 0 to N-1
    do partial pivoting;      // exchange rows if needed
(1). // barrier
    for (j=i+1; j<=N; j++){    // for rows j = i+1 to N
        for (k=i+1; k<=N; k++){ // for columns k = i+1 to N
            f = A[j,i]/A[i,i]; // reduction factor
            A[j,k] -= A[j,k]*f; // reduce row j
        }
        A[j][i] = 0;          // A[j,i] = 0
    }
(2). // barrier
}
(3). // join
```

Step 2: Back Substitution: compute $x_{N-1}, x_{N-2}, \dots, x_0$ in that order

The Gauss elimination algorithm can be parallelized as follows. The algorithm starts with a main thread, which creates N working threads to execute the `ge(thread_id)` function and waits for all the working threads to join. The threads function `ge()` implements the row reduction step of the Gauss elimination algorithm. In the `ge()` function, for each iteration of $\text{row} = 0$ to $N-2$, the thread with $\text{thread_ID}=i$ does the partial pivoting on a corresponding row i . All other threads wait at a barrier (1) until partial pivoting is complete. Then each working thread does row reduction on a unique row equal to its ID number. Since all working threads must have finished the current row reductions before iteration on the next row can start, so they wait at another barrier (2). After reducing the matrix $[A|B]$ to upper triangular form, the final step is to compute the solutions $x[N-i]$, for $i=1$ to N in that order, which is inherently sequential. The main thread must wait until all the working threads have ended before starting the back substitution. This is achieved by join operations by the main thread. The following shows the complete code of the Example Program C4.5.

```

/** C4.5.c: Gauss Elimination with Partial Pivoting **/
#include <stdio.h>
#include <stdlib.h>
#include <math.h>
#include <pthread.h>

#define N 4
double A[N][N+1];
pthread_barrier_t barrier;

int print_matrix()
{
    int i, j;
    printf("-----\n");
    for(i=0; i<N; i++){
        for(j=0; j<N+1; j++){
            printf("%6.2f ", A[i][j]);
        }
        printf("\n");
    }
}

void *ge(void *arg) // threads function: Gauss elimination
{
    int i, j, prow;
    int myid = (int)arg;
    double temp, factor;
    for(i=0; i<N-1; i++){
        if (i == myid){
            printf("partial pivoting by thread %d on row %d: ", myid, i);
            temp = 0.0; prow = i;
            for (j=i; j<=N; j++){
                if (fabs(A[j][i]) > temp){
                    temp = fabs(A[j][i]);
                    prow = j;
                }
            }
        }
    }
}

```

```

    }
    printf("pivot_row=%d pivot=%6.2f\n", prow, A[prow][i]);
    if (prow != i){ // swap rows
        for (j=i; j<N+1; j++){
            temp = A[i][j];
            A[i][j] = A[prow][j];
            A[prow][j] = temp;
        }
    }
}
// wait for partial pivoting done
pthread_barrier_wait(&barrier);
for(j=i+1; j<N; j++){
    if (j == myid){
        printf("thread %d do row %d\n", myid, j);
        factor = A[j][i]/A[i][i];
        for (k=i+1; k<=N; k++)
            A[j][k] -= A[i][k]*factor;
        A[j][i] = 0.0;
    }
}
// wait for current row reductions to finish
pthread_barrier_wait(&barrier);
if (i == myid)
    print_matrix();
}
}

int main(int argc, char *argv[])
{
    int i, j;
    double sum;
    pthread_t threads[N];

    printf("main: initialize matrix A[N][N+1] as [A|B]\n");
    for (i=0; i<N; i++)
        for (j=0; j<N; j++)
            A[i][j] = 1.0;
    for (i=0; i<N; i++)
        A[i][N-i-1] = 1.0*N;
    for (i=0; i<N; i++){
        A[i][N] = 2.0*N - 1;
    }
    print_matrix(); // show initial matrix [A|B]

    pthread_barrier_init(&barrier, NULL, N); // set up barrier

    printf("main: create N=%d working threads\n", N);
    for (i=0; i<N; i++){
        pthread_create(&threads[i], NULL, ge, (void *)i);
    }
}

```

```

printf("main: wait for all %d working threads to join\n", N);
for (i=0; i<N; i++){
    pthread_join(threads[i], NULL);
}
printf("main: back substitution : ");
for (i=N-1; i>=0; i--){
    sum = 0.0;
    for (j=i+1; j<N; j++)
        sum += A[i][j]*A[j][N];
    A[i][N] = (A[i][N]- sum)/A[i][i];
}
// print solution
printf("The solution is :\n");
for(i=0; i<N; i++){
    printf("%6.2f ", A[i][N]);
}
printf("\n");
}

```

Figure 4.5 shows the sample outputs of running the Example 4.6 program, which solves a system of equations with $N=4$ unknowns by Gauss elimination with partial pivoting.

```

main: initialize matrix A[N][N+1] as [A|B]
-----
1.00  1.00  1.00  4.00  7.00
1.00  1.00  4.00  1.00  7.00
1.00  4.00  1.00  1.00  7.00
4.00  1.00  1.00  1.00  7.00
main: create N=4 working threads
partial pivoting by thread 0 on row 0: pivot_row=3 pivot= 4.00
main: wait for all 4 working threads to join
thread 1 do row 1
thread 2 do row 2
thread 3 do row 3
-----
4.00  1.00  1.00  1.00  7.00
0.00  0.75  3.75  0.75  5.25
0.00  3.75  0.75  0.75  5.25
0.00  0.75  0.75  3.75  5.25
partial pivoting by thread 1 on row 1: pivot_row=2 pivot= 3.75
thread 3 do row 3
thread 2 do row 2
partial pivoting by thread 2 on row 2: pivot_row=2 pivot= 3.60
-----
4.00  1.00  1.00  1.00  7.00
0.00  3.75  0.75  0.75  5.25
0.00  0.00  3.60  0.60  4.20
0.00  0.00  0.60  3.60  4.20
thread 3 do row 3
-----
4.00  1.00  1.00  1.00  7.00
0.00  3.75  0.75  0.75  5.25
0.00  0.00  3.60  0.60  4.20
0.00  0.00  0.00  3.50  3.50
main: back substitution : The solution is :
1.00  1.00  1.00  1.00

```

Fig. 4.5 Sample Outputs of Example 4.6 Program

4.6.8 Threads in Linux

Unlike many other operating systems, Linux does not distinguish processes from threads. To the Linux kernel, a thread is merely a process that shares certain resources with other processes. In Linux both processes and threads are created by the `clone()` system call, which has the prototype

```
int clone(int (*fn)(void *), void *child_stack, int flags, void *arg)
```

As can be seen, `clone()` is more like a thread creation function. It creates a child process to execute a function `fn(arg)` with a `child_stack`. The `flags` field specifies the resources to be shared by the parent and child, which includes

CLONE_VM: parent and child share address space

CLONE_FS: parent and child share file system information, e.g. root. CWD

CLONE_FILES: parent and child share opened files

CLONE_SIGHAND: parent and child share signal handlers and blocked signals

If any of the flags is specified, both processes share exactly the SAME resource, not a separate copy of the resource. If a flag is not specified, the child process usually gets a separate copy of the resource. In this case, changes made to a resource by one process do not affect the resource of the other process. The Linux kernel retains `fork()` as a system call but it may be implemented as a library wrapper that calls `clone()` with appropriate flags. An average user does not have to worry about such details. It suffices to say that Linux has an efficient way of supporting threads. Moreover, most current Linux kernels support Symmetric Multiprocessing (SMP). In such Linux systems, processes (threads) are scheduled to run on multiprocessors in parallel.

4.7 Programming Project: User-Level Threads

The programming project is to implement **user-level threads** to simulate threads operations in Linux. The project consists of 4 parts. Part 1 presents the base code of the project to help the reader get started. The base code implements a multitasking system, which supports independent executions of tasks within a Linux process. It is the same MT multitasking system presented in Chap. 3, but adapted to the user-level threads environment. Part 2 is to extend the base code to implement support for task join operation. Part 3 is to extend the base code to support mutex operations. Part 4 is to implement counting semaphores to support task cooperation, and demonstrate semaphores in the multitasking system.

4.7.1 Project Base Code: A Multitasking System

Programming Project PART 1: Base Code: The following shows the base code of the programming project, which will be explained in latter sections.

- (1). **ts.s file** in 32-bit GCC assembly code:

```

#----- ts.s file -----
.global tswitch, running, scheduler
tswitch:
SAVE:    pushal
         pushfl
         movl   running,%ebx
         movl   %esp, 4(%ebx) # integers in GCC are 4 bytes
FIND:    call   scheduler
RESUME:  movl   running, %ebx
         movl   4(%ebx), %esp
         popfl
         popal
         ret

```

- (2). **type.h file:** This file defines the system constants and the PROC structure

```

/****** type.h file *****/
#define NPROC    9
#define SSIZE 1024
// PROC status
#define FREE     0
#define READY   1
#define SLEEP    2
#define BLOCK    3
#define ZOMBIE   4

typedef struct proc{
    struct proc *next;    // next proc pointer
    int ksp;              // saved stack pointer
    int pid;              // proc PID
    int priority;         // proc scheduling priority
    int status;           // current status: FREE|READY, etc.
    int event;            // for sleep/wakeup
    int exitStatus;       // exit status
    int joinPid;           // join target pid
    struct proc *joinPtr; // join target PROC pointer
    int stack[SSIZE];     // proc 4KB stack area
}PROC;

```

- (3). **queue.c file**, which implements queue operation functions

```
// same as in MT system of Chapter 3
```

- (4). **t.c file**, which is the main file of the program

```

#include <stdio.h>
#include "type.h"

```

```

PROC proc[NPROC];           // NPROC proc structures
PROC *freeList;             // free PROC list
PROC *readyQueue;          // ready proc priority queue
PROC *sleepList;           // sleep PROC list
PROC *running;             // running proc pointer
#include "queue.c"         // enqueue(), dequeue(), printList()

int init()
{
    int i, j;
    PROC *p;
    for (i=0; i<NPROC; i++){
        p = &proc[i];
        p->pid = i;
        p->priority = 0;
        p->status = FREE;
        p->event = 0;
        p->joinPid = 0;
        p->joinPtr = 0;
        p->next = p+1;
    }
    proc[NPROC-1].next = 0;
    freeList = &proc[0];    // all PROCs in freeList
    readyQueue = 0;
    sleepList = 0;
    // create P0 as initial running task
    running = p = dequeue(&freeList);
    p->status = READY;
    p->priority = 0;
    printList("freeList", freeList);
    printf("init complete: P0 running\n");
}

int texit(int value)
{
    printf("task %d in texit value=%d\n", running->pid, running->pid);
    running->status = FREE;
    running->priority = 0;
    enqueue(&freeList, running);
    printList("freeList", freeList);
    tswitch();
}

int do_create()
{
    int pid = create(func, running->pid); // parm = pid
}

```

```

int do_switch()
{
    tswitch();
}

int do_exit()
{
    texit(running->pid); // for simplicity: exit with pid value
}

void func(void *parm)
{
    int c;
    printf("task %d start: parm = %d\n", running->pid, (int)parm);
    while(1){
        printf("task %d running\n", running->pid);
        printList("readyQueue", readyQueue);
        printf("enter a key [c|s|q] : ");
        c = getchar(); getchar();
        switch (c){
            case 'c' : do_create(); break;
            case 's' : do_switch(); break;
            case 'q' : do_exit(); break;
        }
    }
}

int create(void (*f)(), void *parm)
{
    int i;
    PROC *p = dequeue(&freeList);
    if (!p){
        printf("create failed\n");
        return -1;
    }
    p->status = READY;
    p->priority = 1;
    p->joinPid = 0;
    p->joinPtr = 0;

    // initialize new task stack for it to resume to f(parm)
    for (i=1; i<13; i++)           # zero out stack cells
        p->stack[SSIZE-i] = 0;
    p->stack[SSIZE-1] = (int)parm;  # function parameter
    p->stack[SSIZE-2] = (int)do_exit; # function return address
    p->stack[SSIZE-3] = (int)f;     # function entry
    p->ksp = (int)&p->stack[SSIZE-12]; # ksp -> stack top
    enqueue(&readyQueue, p);
    printList("readyQueue", readyQueue);
    printf("task %d created a new task %d\n", running->pid, p->pid);
    return p->pid;
}

```

```

}

int main()
{
    printf("Welcome to the MT User-Level Threads System\n");
    init();
    create((void *)func, 0);
    printf("P0 switch to P1\n");
    while(1){
        if (readyQueue)
            tswitch();
    }
}

int scheduler()
{
    if (running->status == READY)
        enqueue(&readyQueue, running);
    running = dequeue(&readyQueue);
    printf("next running = %d\n", running->pid);
}

```

To compile and run the base code under Linux, enter

```
gcc -m32 t.c ts.s
```

Then run a.out. While running the program, the reader may enter the commands

- 'c': create a new task
- 's': switch to run the next task from readyQueue
- 'q': let the running task terminate

to test and observe task executions in the system. Figure 4.6 shows the sample outputs of running the base code program.

4.7.2 User-Level Threads

The entire base code program runs as a Linux process in user mode. Inside the Linux process are independent execution entities, which are equivalent to conventional threads. In order not to be confused with either Linux process or threads, we shall refer to the execution entities as tasks. In the system, tasks run concurrently by multitasking. Figure 4.7 shows the model of concurrent tasks inside a Linux process.

Since all the tasks execute inside a Linux process, the Linux kernel does not know their existence. To the Linux kernel, the entire MT system is a single Linux process, but we subdivide the CPU's execution time to run different tasks inside the Linux process. For this reason, the tasks are known as **user-level threads**. The purpose of this programming project is to create a multitasking environment in a Linux process to support user-level threads. The same technique can also be used to create user-level threads under any operating system. Next, we explain the base code in more detail by the following steps.

```

Welcome to the MT User-Level Threads System
freeList = [1 0]->[2 0]->[3 0]->[4 0]->[5 0]->[6 0]->[7 0]->[8 0]->NULL
init complete
readyQueue = [1 1]->NULL
task 0 created a new task 1
P0 switch to P1
next running = 1
task 1 start: parm = 0
task 1 running
readyQueue = [0 0]->NULL
enter a key [c|s|q] : c
readyQueue = [2 1]->[0 0]->NULL
task 1 created a new task 2
task 1 running
readyQueue = [2 1]->[0 0]->NULL
enter a key [c|s|q] : s
next running = 2
task 2 start: parm = 1
task 2 running
readyQueue = [1 1]->[0 0]->NULL
enter a key [c|s|q] : q
task 2 in texit value=2
freeList = [3 0]->[4 0]->[5 0]->[6 0]->[7 0]->[8 0]->[2 0]->NULL
next running = 1
task 1 running
readyQueue = [0 0]->NULL
enter a key [c|s|q] : █

```

Fig. 4.6 Sample Outputs of the Base Code Program

Fig. 4.7 Concurrent Tasks
in a Linux Process

```

----- a.out = Linux Process -----
|           (concurrent tasks)           |
|   task1   task2   . . .   taskn   |
|           |           |           |
|-----|-----|-----|-----|

```

- (1). **Task PROC structure:** A major difference between processes and threads is that the former obey a parent-child relation but the latter do not. In the threads model, all threads are equal. Relations between threads are peer-to-peer, rather than parent to child. So there is no need for parent task PID and the task family tree. Therefore, these fields are deleted from the PROC structure. The new fields joinPid and joinPtr are for implementing the threads join operation, which will be discussed later.
- (2). **init():** When the system starts, main() calls init() to initialize the system. Init() initializes the PROC structures and enter them into a freeList. It also initializes the readyQueue to empty. Then it uses proc[0] to creates P0 as the initial running task. P0 has the lowest priority 0. All other tasks have a priority 1, so that they will take turn to run from the readyQueue.
- (3). P0 calls create() to create a task P1 to execute the func(parm) function with a parameter parm=0, and enters it into the readyQueue. Then P0 calls tswitch() to switch task to run P1.
- (4). **tswitch():** The tswitch() function implements task context switching. Instead of push/pop individual CPU registers, it uses the PUSHAL and POPAL instructions. tswitch() acts as a task switch box, where one task goes in and, in general, another tasks emerges. It consists of 3 separated steps, which are explained in more detail below.
 - (4).1. **SAVE part of tswitch():** When a task calls tswitch(), it saves the return address on its own stack and enters tswitch() in assembly code. In tswitch(), the SAVE part saves CPU registers into the calling task's stack, save the stack pointer into proc.ksp. The Intel x86 CPU in 32-bit mode has many registers, but only the registers eax, ebx, ecx, edx, esp, ebp, esi, edi and eflags are visible to

user mode processes. So we only need to save and restore these registers while a (Linux) process is executing. The following diagram shows the stack contents and the saved stack pointer of the calling task after executing the SAVE part of `tswitch()`, where `xxx` denote the stack contents before calling `tswitch()`.

```

                                proc.ksp
                                |
|xxx|retPC|eax|ecx|edx|ebx|old_esp|ebp|esi|edi|eflags|

```

In the Intel x86 based PCs in 32-bit mode, every CPU register is 4 bytes wide and stack operations are always in units of 4 bytes. Thus, we may define the PROC stack as an integer array.

- (4).2. **scheduler()**: After executing the SAVE part of `tswitch()`, the task calls `scheduler()` to pick the next running task. In `scheduler()`, if the calling task is still **READY** to run, it calls `enqueue()` to put itself into the `readyQueue` by priority. Otherwise, the task will not be in `readyQueue`, which makes it non-runnable. Then it calls `dequeue()`, which returns the first ready PROC removed from `readyQueue` as the next running task.
- (4).3. **RESUME part of tswitch()**: When execution returns from `scheduler()`, running may have changed to point at the PROC of a different task. The RESUME part of `tswitch()` sets the CPU's stack pointer to the saved stack pointer of the current running task. Then it pops saved registers, followed by RET, causing the current running task return to where it called `tswitch()` earlier.
- (5). **create()**: The `create(func, parm)` function creates a new task and enters it into the `readyQueue`. The new task will begin execution from the named `func()` function with `parm` as parameter. Although the new task never existed before, we may pretend it not only existed before but also ran before. The reason why it is not running now is because it called `tswitch()` to give up CPU earlier. If so, its stack must contain a frame saved by the SAVE part of `tswitch()`, and its saved `ksp` must point at the stack top. Furthermore, when a new task begins execution from `func()`, which is written as `func(void *parm)`, it must have a return address and a parameter `parm` on the stack. When `func()` finishes, the task shall "return to where `func()` was called earlier". Thus, in `create()`, we initialize the stack of the new task as follows.

```

                                proc.ksp
                                |< ----- all saved registers = 0- -----> |
|parm|do_exit|func|eax|ecx|edx|ebx|oldesp|ebp|esi|edi|eflags|
  -1   -2    -3   -4  -5  -6  -7    -8   -9 -10 -11  -12

```

where the index `-i` means `SSIZE-i`. These are done by the following code segment in `create()`.

```

for (i=1; i<13; i++)           # zero out stack cells
    p->stack[SSIZE-i] = 0;
p->stack[SSIZE-1] = (int)parm;   # function parameter
p->stack[SSIZE-2] = (int)do_exit; # function return address
p->stack[SSIZE-3] = (int)func;   # function entry
p->ksp = (int)&p->stack[SSIZE-12]; # ksp -> stack top

```

When the new task begins to run, it executes the RESUME part of `tswitch()`, causing it to return to the entry address of `func()`. When execution enters `func()`, the stack top contains a pointer to `do_exit()` and a parameter `parm`, as if it was called as `func(parm)` from the entry address of `do_exit()`. In practice, the task function rarely returns. If it does, it would return to `do_texit()`, which causes the task to terminate.

- (5). **func()**: For demonstration purpose, all tasks are created to execute the same function, func(parm). For simplicity, the function parameter is set to the pid of the creator task, but the reader may pass any parameter, e.g. a structure pointer, to the function. While executing in func(), a task prompts for a command char = [c | s | q], where

‘c’ : create a new task to execute func(parm), with parm=caller pid
 ‘s’ : switch task;
 ‘q’ : terminate and return the PROC as FREE to freeList

- (6). **The Idle Task P0**: P0 is special in that it has the lowest priority among all the tasks. After system initialization, P0 creates P1 and switches to run P1. P0 will run again if and only if there are no runnable tasks. In that case, P0 simply loops. The reader may enter Control-C to terminate the (Linux) process. It is noted that the stack of P0 is actually the user mode stack of the Linux process.

4.7.3 Implementation of Thread Join Operation

PART 2: Extend Base Code to support task join operation. The extensions are listed in order below.

- (1). **tsleep(int event)**: Whenever a task must wait for something that’s not available, it calls tsleep() to go to sleep on an event value, which represents the reason of the sleep. The algorithm of tsleep() is

```

/***** Algorithm of tsleep(int event) *****/
1. record event value in proc.event:  running->event = event;
2. change status to SLEEP:           running->status = SLEEP;
3. for ease of maintenance, enter caller into a (global) PROC *sleepList:
   enqueue(&sleepList, running);
4. give up CPU:                       tswitch();

```

A sleeping task is not runnable until it is woken up by another task. So in tsleep(), the task calls tswitch() to give up the CPU.

- (2). **int twakeup(int event)**: twakeup() wakes up ALL tasks that are sleeping on the specified event value. If no task is sleeping on the event, it does nothing. The algorithm of twakeup() is

```

/***** Algorithm of twakeup(int event) *****/
for each PROC *p in sleepList do{ // assume sleepers are in a global sleepList
    if (p->event == event){
        delete p from sleepList;
        p->status = READY;           // make p READY to run again
        enqueue(&readyQueue, p);    // enter p into readyQueue by priority
    }
}

```

- (3). **texit(int status)**: Modified texit() in the base code for tasks to terminate. In the process model, every process has a unique parent (which may be the INIT process P1), which always waits for the process to terminate. So a terminating process can become a ZOMBIE and wakes up its parent, which will dispose of the ZOMBIE child. If a terminating process has children, it must give away the children to either the INIT process or a subreaper process before becoming a ZOMBIE. In the threads model, threads are all equal. A thread does not have a parent or children. When a thread

terminates, if there is no other threads waiting for it to terminate, it must exit as FREE. If there is any thread waiting for it to terminate, it should become a ZOMBIE, wake up all such threads, allowing one of them to find and dispose of the ZOMBIE. In the threads model, the thread termination algorithm is

```

/***** Algorithm of texit(int status) *****/
1.  try to find a (any) task which wants to join with this task;
2.  if no task wants to join with this task: exit as FREE
    // some task is waiting for this task to terminate
3.  record status value in proc.exitStatus: running->exitStatus = status;
4.  become a ZOMBIE:                running->status = ZOMBIE;
5.  wake up joining tasks:          twakeup(running->pid)
6.  give up CPU:                    tswitch();

```

- (4). **join(int targetPid, int *status)**: The join operation waits for a thread with targetPid to terminate. In the process model, every process can only be waited by a unique parent, and a process never waits for its own parent to terminate. So the waiting sequence is always a unidirectional chain. In the threads model, a thread is allowed to join with any other thread. This may cause two problems. First, when a thread tries to join with a target thread, the target thread may no longer exist. In this case, the joining thread must return with an error. If the target thread exists but has not terminated yet, the joining thread must go to sleep on the target thread PID, waiting for the target thread to terminate. Second, since threads do not obey the parent-child relation, a sequence of joining threads may lead to a deadlock waiting loop. In order to prevent such deadlocks, every joining thread must record the identity of the target thread in its PROC structure to allow other joining threads to check whether the join request would lead to a deadlock. When the targeted thread terminates, it can check whether there are any threads waiting for it to terminate. If so, it would become a ZOMBIE and wake up all such joining threads. Upon waking up, the joining threads must execute the join operation again since the ZOMBIE may already be freed by another joining thread. Thus, the algorithm of the thread join operation is as follows.

```

/***** Algorithm of join(int targetPid, int *status) *****/
while(1)
{
  1.  if (no task with targetPid) return NOPID error;
  2.  if (targetPid's joinPtr list leads to this task) return DEADLOCK error;
  3.  set running->joinPid = targetPid, running->joinPtr ->targetPid's PROC;
  4.  if (found targetPid's ZOMBIE proc *p){
      *status = p->exitStatus; // extract ZOMBIE exit status
      p->status = FREE; p->priority = 0;
      enqueue(&freeList, p); // release p to freeList
      return p->pid;
    }
  5.  tsleep(targetPid); // sleep on targetPID until woken up by target task
}

```

Steps 2 of the join() algorithm prevents deadlock due to either crossed or circular joining requests, which can be checked by traversing the targetPid's joinPtr pointer list. Each joining task's joinPtr points to a target PROC it intends to join with. If the list points back to the current running task, it would be a circular waiting list, which must be rejected due to a potential deadlock.

Programming Project PART 2: Part 2 of the programming project is for the reader to implement the `tsleep()`, `twakeup()` and `join()` functions. Then test the resulting system by the following program code, which uses task creation and join operations of the programming project.

```

/***** PART 2 of Programming Project *****/
#include <stdio.h>
#include <stdlib.h>
#include "type.h"

PROC proc[NPROC];
PROC *freeList;
PROC *sleepList;
PROC *readyQueue;
PROC *running;

/***** implement these functions *****/
int tsleep(int event){ }
int twakeup(int event){ }
int texit(int status){ }
int join(int pid, int *status){ }
/***** end of implementations *****/

int init(){ } // SAME AS in PART 1

int do_exit()
{
    // for simplicity: exit with pid value as status
    texit(running->pid);
}

void task1(void *parm) // task1: demonstrate create-join operations
{
    int pid[2];
    int i, status;
    //printf("task %d create subtasks\n", running->pid);
    for (i=0; i<2; i++){ // P1 creates P2, P3
        pid[i] = create(func, running->pid);
    }
    join(5, &status); // try to join with targetPid=5
    for (i=0; i<2; i++){ // try to join with P2, P3
        pid[i] = join(pid[i], &status);
        printf("task%d joined with task%d: status = %d\n",
            running->pid, pid[i], status);
    }
}

void func(void *parm) // subtasks: enter q to exit
{
    char c;
    printf("task %d start: parm = %d\n", running->pid, parm);
    while(1){

```

```

    printList("readyQueue", readyQueue);
    printf("task %d running\n", running->pid);
    printf("enter a key [c|s|q|j]: ");
    c = getchar(); getchar(); // kill \r
    switch (c){
        case 'c' : do_create(); break;
        case 's' : do_switch(); break;
        case 'q' : do_exit(); break;
        case 'j' : do_join(); break;
    }
}
}

int create(void (*f)(), void *parm)
{
    int i;
    PROC *p = dequeue(&freeList);
    if (!p){
        printf("create failed\n");
        return -1;
    }
    p->status = READY;
    p->priority = 1;
    p->joinPid = 0;
    p->joinPtr = 0;
    for (i=1; i<13; i++)
        p->stack[SSIZE-i] = 0;
    p->stack[SSIZE-1] = (int)parm;
    p->stack[SSIZE-2] = (int)do_exit;
    p->stack[SSIZE-3] = (int)f;
    p->ksp = &p->stack[SSIZE-12];

    enqueue(&readyQueue, p);
    printList("readyQueue", readyQueue);
    printf("task%d created a new task%d\n", running->pid, p->pid);
    return p->pid;
}

int main()
{
    int i, pid, status;
    printf("Welcome to the MT User-Threads System\n");
    init();
    create((void *)task1, 0);
    printf("P0 switch to P1\n");
    tswitch();
    printf("All tasks ended: P0 loops\n");
    while(1);
}

```

```

Welcome to the MT User-Level Threads System
freelist = 1 --> 2 --> 3 --> 4 --> 5 --> 6 --> 7 --> 8 --> NULL
init complete
task0 create a new task 1
P0 switch to P1
task 1 running
task1 create a new task 2
task1 create a new task 3
task1 try to join with task5: join error: no such pid 5
task1 try to join with task2: sleepList = 1 --> NULL
readyQueue = 3 --> 0 --> NULL
task 2 running: enter a key [c|s|q|j]: j
enter a pid to join with : 1
task2 try to join with task1: join error: DEADLOCK
readyQueue = 3 --> 0 --> NULL
task 2 running: enter a key [c|s|q|j]: q
readyQueue = 3 --> 1 --> 0 --> NULL
task 2 exited with status = 2
readyQueue = 1 --> 0 --> NULL
task 3 running: enter a key [c|s|q|j]: q
task 3: no joiner=>exit as FREE: task 3 exited with status = 3
task1 joined with task2 status = 2
task1 try to join with task3: join error: no such pid 3
task 1: no joiner=>exit as FREE: task 1 exited with status = 1
All tasks ended: P0 loops

```

Fig. 4.8 Sample Outputs of Task Join Program

```

int scheduler()
{
    if (running->status == READY)
        enqueue(&readyQueue, running);
    running = dequeue(&readyQueue);
}

```

In the test program, P0 creates a new task P1, which executes the function task1(). When P1 runs, it creates two new tasks P2 and P3 to execute the function func(). P1 first tries to join the targetPid = 5. Then it tries to join with both P2 and P3. Figure 4.8 shows the sample outputs of running Part 2 of the Project Program, which demonstrates task join operations. As the figure shows, when P1 tries to join with P5, it results in a join error due to invalid targetPid. Then P1 tries to join with task 2, which causes it to wait. When P2 runs, it tries to join with P1, which is rejected because this would lead to a deadlock. Then P2 exits, which switches task to run P3. When P3 exits, P1 is still waiting to join with P2, so P3 exits as FREE, allowing P1 to complete its join operation with P2. When P1 tries to join with P3, it gets an invalid targetPid error since P3 no longer exists. Instead of letting P3 exit first, the reader may let P3 switch to P1, which will dispose of the ZOMBIE P2 and then tries to join with P3. In that case, when P3 exits, P1 will complete its join operation with P3 successfully. The reader may modify the test program to create more tasks and enter different command sequences to test the system.

4.7.4 Implementation of Mutex Operations

Programming Project PART 3: Extend Part 2 of the project to support mutex operations. The extensions are described below.

(1). Mutex Structure

```

typedef struct mutex{
    int lock;      // mutex lock state: 0 for unlocked, 1 for locked
    PROC *owner;  // pointer to owner of mutex; may also use PID
    PROC *queue;  // FIFO queue of BLOCKED waiting PROCs
};MUTEX;

MUTEX *mutex_create() // create a mutex and initialize it
{
    MUTEX *mp = (MUTEX *)malloc(sizeof(MUTEX));
    mp->lock = mp->owner = mp->queue = 0;
    return mp;
}

void mutex_destroy(MUTEX *mp){ free(mp); }
int mutex_lock(MUTEX *mp){ // implement mutex locking operation }
int mutex_unlock(MUTEX *mp){// implement mutex unlocking operation }

/***** Algorithm of mutex_lock() *****/
(1). if (mutex is in unlocked state){
    change mutex to locked state;
    record caller as mutex owner;
}
(2). else{
    BLOCK caller in mutex waiting queue;
    switch task;
}

/***** Algorithm of mutex_unlock() *****/
(1). if (mutex is unlocked || (mutex is locked && caller NOT owner))
    return error;
(2). // mutex is locked && caller is owner
    if (no waiter in mutex waiting queue){
        change mutex to unlocked state;
        clear mutex owner field to 0;
    }
(3). else{ // mutex has waiters
    PROC *p = dequeue a waiter from mutex waiting queue;
    change mutex owner to p; // mutex remains locked
    enter p into readyQueue;
}

```

4.7.5 Test Project with Mutex by Concurrent Programs

Part 3: Implement `mutex_lock()` and `mutex_unlock()` functions for the MT system. Test mutex operations by the following program. The test program is a modified version of the Example 4.3 program using Pthreads. It computes the sum of the elements of a matrix by concurrent tasks and mutex

of the MT system. In the test program, P0 initializes a 4×4 matrix, creates P1 to execute task1(). P1 creates 4 working tasks to execute the function func(parm). Each working task computes the partial sum of a row and updates the global variable total using mutex for synchronization. The outputs should look like Fig. 4.9.

```

/***** test program for mutex operations *****/
#include <stdio.h>
#include <stdlib.h>
#include "type.h"

PROC proc[NPROC], *freeList, *sleepList, *readyQueue, *running;

#include "queue.c" // queue operation functions
#include "wait.c" // tsleep/twakeup/texit/join functions
#include "mutex.c" // mutex operation functions

#define N 4
int A[N][N]; // matrix A
MUTEX *mp; // mutex for task synchronization
int total; // global total

int init()
{
    int i, j;
    PROC *p;
    for (i=0; i<NPROC; i++){
        p = &proc[i];
        p->pid = i;
        p->ppid = 1;
        p->priority = 0;
        p->status = FREE;
        p->event = 0;
        p->next = p+1;
    }
    proc[NPROC-1].next = 0;
    freeList = &proc[0];
    readyQueue = 0;
    sleepList = 0;
    p = running = dequeue(&freeList);
    p->status = READY;
    p->priority = 0;
    printList("freeList", freeList);

    printf("P0: initialize A matrix\n");
    for (i=0; i<N; i++){
        for (j=0; j<N; j++){
            A[i][j] = i*N + j + 1;
        }
    }
}

```

```

for (i=0; i<N; i++){ // show the matrix
    for (j=0; j<N; j++){
        printf("%4d ", A[i][j]);
    }
    printf("\n");
}
mp = mutex_create(); // create a mutex
total = 0;
printf("init complete\n");
}

int myexit() // for task exit
{
    texit(0);
}

void func(void *arg)
{
    int i, row, s;
    int me = running->pid;
    row = (int)arg;
    printf("task %d computes sum of row %d\n", me, row);
    s = 0;
    for (i=0; i < N; i++){
        s += A[row][i];
    }
    printf("task %d update total with %d\n", me, s);
    mutex_lock(mp);
    total += s;
    printf("[total = %d] ", total);
    mutex_unlock(mp);
}

void task1(void *parm)
{
    int pid[N];
    int i, status;
    int me = running->pid;
    printf("task %d: create working tasks : ", me);
    for(i=0; i < N; i++) {
        pid[i] = create(func, (void *)i);
        printf("%d ", pid[i]);
    }
    printf(" to compute matrix row sums\n");
    for(i=0; i<N; i++) {
        printf("task %d tries to join with task %d\n",
            running->pid, pid[i]);
        join(pid[i], &status);
    }
}

```

```

    printf("task %d : total = %d\n", me, total);
}

int create(void (*f)(), void *parm)
{
    int i;
    PROC *p = dequeue(&freeList);
    if (!p){
        printf("fork failed\n");
        return -1;
    }
    p->ppid = running->pid;
    p->status = READY;
    p->priority = 1;
    p->joinPid = 0;
    p->joinPtr = 0;
    for (i=1; i<12; i++){
        p->stack[SSIZE-i] = 0;
        p->stack[SSIZE-1] = (int)parm;
        p->stack[SSIZE-2] = (int)myexit;
        p->stack[SSIZE-3] = (int)f;
        p->ksp = &p->stack[SSIZE-12];
    }
    enqueue(&readyQueue, p);
    return p->pid;
}

int main()
{
    printf("Welcome to the MT User-Level Threads System\n");
    init();
    create((void *)task1, 0);
    //printf("P0 switch to P1\n");
    tswitch();
    printf("all task ended: P0 loops\n");
    while(1);
}

int scheduler()
{
    if (running->status == READY)
        enqueue(&readyQueue, running);
    running = dequeue(&readyQueue);
}

```

Figure 4.9 shows the sample outputs of running the test program of mutex.

```

Welcome to the MT User-Level Threads System
freeList = 1 --> 2 --> 3 --> 4 --> 5 --> 6 --> 7 --> 8 --> NULL
P0: initialize A matrix
  1  2  3  4
  5  6  7  8
  9 10 11 12
 13 14 15 16
init complete
task 1: create working tasks : 2 3 4 5 to compute matrix row sums
task 1 tries to join with task 2
sleepList = 1 --> NULL
task 2 computes sum of row 0
task 2 update total with 10
task 2 mutex_lock() [total = 10] task 2 mutex_unlock()
task 3 computes sum of row 1
task 3 update total with 26
task 3 mutex_lock() [total = 36] task 3 mutex_unlock()
task 4 computes sum of row 2
task 4 update total with 42
task 4 mutex_lock() [total = 78] task 4 mutex_unlock()
task 5 computes sum of row 3
task 5 update total with 58
task 5 mutex_lock() [total = 136] task 5 mutex_unlock()
task 1 tries to join with task 3
task 1 tries to join with task 4
task 1 tries to join with task 5
task 1 : tatal = 136
all task ended: P0 loops
■

```

Fig. 4.9 Matrix Sum by Concurrent Tasks and Mutex

4.7.6 Implementation of Semaphores

Programming Project PART 4: Implement counting semaphores as described in Sect. 4.6.5. Demonstrate semaphores by the following test program, which is the producer-consumer problem of Example 4.5 adapted to the MT system.

4.7.7 Producer-Consumer Problem using Semaphores

```

/***** test program for semaphore operations *****/
#include <stdio.h>
#include "type.h"
PROC proc[NPROC], *freeList, *sleepList, *readyQueue, *running;
#include "queue.c" // queue operation function
#include "wait.c" // tsleep/twakeup/texit/join functions

#define NBUF 4
#define N 8
int buf[NBUF], head, tail; // buffers for producer-consumer

typedef struct{
    int value;
    PROC *queue;
}SEMAPHORE;
SEMAPHORE full, empty, mutex; // semaphores

```

```

int P(SEMAPHORE *s)
{ // implement P function }

int V(SEMAPHORE *s)
{ // implement V function }

void producer() // produce task code
{
    int i;
    printf("producer %d start\n", running->pid);
    for (i=0; i<N; i++){
        P(&empty);
        P(&mutex);
        buf[head++] = i+1;
        printf("producer %d: item = %d\n", running->pid, i+1);
        head %= NBUF;
        V(&mutex);
        V(&full);
    }
    printf("producer %d exit\n", running->pid);
}

void consumer() // consumer task code
{
    int i, c;
    printf("consumer %d start\n", running->pid);
    for (i=0; i<N; i++) {
        P(&full);
        P(&mutex);
        c = buf[tail++];
        tail %= NBUF;
        printf("consumer %d: got item = %d\n", running->pid, c);
        V(&mutex);
        V(&empty);
    }
    printf("consumer %d exit\n", running->pid);
}

int init()
{
    int i, j;
    PROC *p;
    for (i=0; i<NPROC; i++){
        p = &proc[i];
        p->pid = i;
        p->ppid = 1;
        p->priority = 0;
        p->status = FREE;
        p->event = 0;
        p->next = p+1;
    }
}

```

```

proc[NPROC-1].next = 0;
freeList = &proc[0];
readyQueue = 0;
sleepList = 0;
p = running = dequeue(&freeList);
p->status = READY;
p->priority = 0;
printList("freeList", freeList);

// initialize semaphores full, empty, mutex
head = tail = 0;
full.value = 0; full.queue = 0;
empty.value=NBUF; empty.queue = 0;
mutex.value = 1; mutex.queue = 0;
printf("init complete\n");
}
int myexit(){ texit(0); }

int task1()
{
    int status;
    printf("task %d creates producer-consumer tasks\n", running->pid);
    create((void *)producer, 0);
    create((void *)consumer, 0);
    join(2, &status);
    join(3, &status);
    printf("task %d exit\n", running->pid);
}

int create(void (*f)(), void *parm)
{
    int i;
    PROC *p = dequeue(&freeList);
    if (!p){
        printf("fork failed\n");
        return -1;
    }
    p->ppid = running->pid;
    p->status = READY;
    p->priority = 1;
    p->joinPid = 0;
    p->joinPtr = 0;
    for (i=1; i<12; i++){
        p->stack[SSIZE-i] = 0;
        p->stack[SSIZE-1] = (int)parm;
        p->stack[SSIZE-2] = (int)myexit;
        p->stack[SSIZE-3] = (int)f;
        p->ksp = &p->stack[SSIZE-12];
    }
    enqueue(&readyQueue, p);
    return p->pid;
}

```

```

int main()
{
    printf("Welcome to the MT User-Level Threads System\n");
    init();
    create((void *)task1, 0);
    printf("P0 switch to P1\n");
    tswitch();
    printf("all task ended: P0 loops\n");
    while(1);
}

int scheduler()
{
    if (running->status == READY)
        enqueue(&readyQueue, running);
    running = dequeue(&readyQueue);
}

```

Figure 4.10 shows the sample outputs of the producer-consumer problem using semaphores.

Solutions to the programming project are available online for download. Source code of the programming project is available for instructors upon request.

```

Welcome to the MT User-Level Threads System
freelist = 1 --> 2 --> 3 --> 4 --> 5 --> 6 --> 7 --> 8 --> NULL
init complete
P0 switch to P1
task 1 creates producer-consumer tasks
sleepList = 1 --> NULL
producer 2 start
producer 2: item = 1
producer 2: item = 2
producer 2: item = 3
producer 2: item = 4
task 2 block on sem=0x80541e8
consumer 3 start
consumer 3: got item = 1
task 3 V up 2 on sem=0x80541e8
consumer 3: got item = 2
consumer 3: got item = 3
consumer 3: got item = 4
task 3 block on sem=0x805420c
producer 2: item = 5
task 2 V up 3 on sem=0x805420c
producer 2: item = 6
producer 2: item = 7
producer 2: item = 8
producer 2 exit
consumer 3: got item = 5
consumer 3: got item = 6
consumer 3: got item = 7
consumer 3: got item = 8
consumer 3 exit
task 1 exit
all task ended: P0 loops
■

```

Fig. 4.10 Producer-Consumer Problem using Semaphores

4.8 Summary

This chapter covers concurrent programming. It introduces the concept of parallel computing and points out its importance. It compares sequential algorithms with parallel algorithms, and parallelism vs. concurrency. It explains the principles of threads and their advantages over processes. It covers threads operations in Pthreads by examples. These include threads management functions, threads synchronization tools of mutex, join, condition variables and barriers. It demonstrates concurrent programming using threads by detailed examples. These include matrix computation, quicksort and solving systems of linear equations by concurrent threads. It explains the deadlock problem and shows how to prevent deadlocks in concurrent programs. It covers semaphores and demonstrates their advantages over condition variables. It also explains the unique way of supporting threads in Linux. The programming project is to implement user-level threads. It presents a base system to help the reader get started. The base system supports dynamic creation, execution and termination of concurrent tasks, which are equivalent to threads executing in the same address space of a process. The project is for the reader to implement threads join, mutex and semaphores for threads synchronization and demonstrate their usage in concurrent programs. The programming project should allow the reader to have a deeper understanding of the principles and techniques of multitasking, threads synchronization and concurrent programming.

Problems

1. Modify the Example Program C4.1 to find the maximum element value of an $N \times N$ matrix by concurrent threads.
2. In the `qsort()` function of the Example Program C4.2, it picks the rightmost element of an unsorted interval as the pivot. Modify it to use the leftmost element as the pivot, and compare the number of sorting steps needed in both cases.
3. Modify the Example Program C4.4 to create multiple producer and consumer threads.
4. Implement the producer-consumer problem using semaphores, as suggested in Example 4.5.
5. In the Example Program C4.5, the number of working threads, N , is equal to the dimension of the A matrix. This may be undesirable if N is large. Modify the program to use `NTHREADS` working threads, where `NTHREADS` $\leq N$. For example, with $N=8$, `NTHREADS` may be 2, 4 or any number $\leq N$.
6. Modify the Example Program C4.1 to compute the sum of all the elements in a matrix by concurrent tasks in the MT system. The results should be the same as in Example 4.1.
7. Assume that in the user-level threads MT system every task will be joined by some task. When the system ends, there should be no ZOMBIE tasks left behind. Implement `textit()` and `join()` to meet these requirements.

References

- Buttlar, D, Farrell, J, Nichols, B., "PThreads Programming, A POSIX Standard for Better Multiprocessing", O'Reilly Media, 1996
- Dijkstra, E.W., Co-operating Sequential Processes, Programming Languages, Academic Press, 1965
- Goldt, S., van der Meer, S. Burkett, S. Welsh, M. The Linux Programmer's Guide, Version 0.4. March 1995.
- IBM MVS Programming Assembler Services Guide, Oz/OS V1R11.0, IBM
- Love, R. Linux Kernel Development, 2nd Edition, Novell Press, 2005
- POSIX.1C, Threads extensions, IEEE Std 1003.1c, 1995
- Pthreads: <https://computing.llnl.gov/tutorials/pthreads>, 2017
- The Linux Man page Project: <https://www.kernel.org/doc/man-pages>, 2017